

Aluminum Service Entrance Heads

For Threaded Rigid Conduit

Threaded

Application:

Threaded type head used with threaded rigid conduit and IMC for pulling service drop conductors

Features:



- Weather resistant
- Assembled with electrical grade phenolic insulator with multiple hole

Standard Materials:

Aluminum
Phenolic Insulator



Type 400



UL Listed:
E155410



CAT. NO.	TRADE SIZE	DIM A	DIM B	NPSM THREAD 'C' SIZE	HOOD + YOKE SCREW 'D' (2Nos.)	INSULATOR 'E' CAP SIZE	UNIT PACK	STD. PACK	WEIGHT (LBS.) PER 100	NAED MFG #78-5994 UPC/DCI #
400	1/2"	2.7462	1.3435	1/2 - 14	10-24 x 1/2	ECI-050	10	50	25	40050
401	3/4"	3.1244	1.4342	3/4 - 14	10-24 x 1/2	ECI-075	10	50	32	40150
402	1"	3.4475	1.7139	1 - 11.5	10-24 x 1/2	ECI-100	10	50	48	40250
403	1-1/4"	4.1567	1.8835	1-1/4 - 11.5	10-24 x 1/2	ECI-125	-	25	53	40350
404	1-1/2"	5.2087	2.1670	1-1/2 - 11.5	10-24 x 1/2	ECI-150	-	10	112	40450
405	2"	6.6744	2.6950	2 - 11.5	10-24 x 1/2	ECI-200	-	5	130	40550
406	2-1/2"	9.3142	3.3057	2-1/2 - 8	5/16 - 18 x 25/32	ECI-250	-	2	416	40650
407	3"	12.2731	4.1252	3 - 8	5/16 - 18 x 25/32	ECI-250	-	1	418	40750
408	3-1/2"	12.7656	4.5940	3-1/2 - 8	5/16 - 18 x 25/32	ECI-300-7	-	1	810	40850
409	4"	12.7656	5.0787	4 - 8	5/16 - 18 x 25/32	ECI-300-6	-	1	835	40950