

**W963 PLYSAFE®  
High Voltage Insulating  
Tape with Liner**

A 30 mil (0,76mm) EPR, self-amalgamating high voltage tape for insulating and jacketing splices through 69kV. W963 Plysafe amalgamates quickly, yielding a void-free, electrically stable build-up and is ideal for water-proofing. ASTM-D-4388, HHI-553C/Grade A, MIL-I-3825B.

**3 BI-SEAL®  
High Voltage Insulating  
Tape with Liner**

A polyethylene and ethylene propylene rubber based tape possessing superior electrical, chemical, mechanical and thermal properties. Fuses quickly, yielding a void-free, electrically stable build-up. For insulating and jacketing of splices on power cable from 600 volts through 69kV and for building stress cones and jacketing of terminations on power cable from 600 volts through 35kV. Available in 20 mil (0,51mm) or 30 mil (0,76mm) thickness. ASTM-D-4388, HHI-553C.

**HIGH  
VOLTAGE  
TAPE**



**W963 PLYSAFE® High Voltage Insulating Tape with Liner**

Cat.	Dimensions	Packaging	Weight
2117	3/4" x .030" x 30' 19mm x 0,76mm x 9,1m	60/case B	26 lbs 12 kg
2132	1" x .030" x 30' 25mm x 0,76mm x 9,1m	40/case B	24 lbs 11 kg
2134	1 1/2" x .030" x 30' 38mm x 0,76mm x 9,1m	30/case B	26 lbs 12 kg
2145	2" x .030" x 30' 50mm x 0,76mm x 9,1m	40/case C	44 lbs 20 kg

**3 BI-SEAL® High Voltage Insulating Tape with Liner**

Cat.	Dimensions	Packaging	Weight
8051	3/4" x .020" x 30' 19mm x 0,51mm x 9,1m	100/case C	30 lbs 14 kg
8052	1" x .020" x 30' 25mm x 0,51mm x 9,1m	80/case C	33 lbs 15 kg
8053	1 1/2" x .020" x 30' 38mm x 0,51mm x 9,1m	50/case C	30 lbs 14 kg
8054	2" x .020" x 30' 50mm x 0,51mm x 9,1m	40/case C	33 lbs 15 kg
8065	3/4" x .030" x 30' 19mm x 0,76mm x 9,1m	100/case C	40 lbs 18 kg
8066	1" x .030" x 30' 25mm x 0,76mm x 9,1m	80/case C	43 lbs 20 kg
8067	1 1/2" x .030" x 30' 38mm x 0,76mm x 9,1m	50/case C	40 lbs 18 kg
8068	2" x .030" x 30' 50mm x 0,76mm x 9,1m	40/case C	43 lbs 20 kg