

CATEGORY 1

Professional Industrial-Grade PVC Specialty Cement

750™ HOTWELD PVC Blue, Medium-Bodied, Extremely Fast-Setting NEW



- Medium-bodied, fast-setting, PVC solvent cement for use on rigid PVC with interference fit Sch. 40 through 6" and Sch. 80 through 4"
- Premium, hot blue formulation, excellent for use in challenging conditions including wet, damp or cold applications with superior long-term performance

- One-step cement that can be used without primer on Sch. 40 pipe and fittings if local code permits
- Low-VOC formulation that complies with LEED requirements



Product Code	Product Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
13754	¼ Pt. Can with Applicator Cap	13754	012181-137543	0.29	24	8
13753	½ Pt. Can with Applicator Cap	13753	012181-137536	0.41	24	15
13752	Pt. Can with Applicator Cap	13752	012181-137529	0.42	12	14
13751	Qt. Can with Applicator Cap	13751	012181-137512	0.78	12	28
13750	Gal. Can with Screw-on Cap	13750	012181-137505	1.21	6	53

725™ PVC Wet 'R Dry™ Aqua Blue, Medium-Bodied, Extremely Fast-Setting



- Medium-bodied, extremely fast-setting, low-VOC PVC cement for all classes and schedules with interference fit through 6" (160 mm) diameter, Schedule 80 through 4" (110 mm) diameter
- Premium formula for wet conditions and/or quick pressurization

- Suitable for irrigation, plumbing, and pool & spa applications
- Can be used without primer on non-pressure systems if local codes permit



Product Code	Product Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
10850	¼ Pt. Can with Applicator Cap	107250951	012181-108505	0.29	24	8
10167	½ Pt. Can with Applicator Cap	107250941	012181-101674	0.41	24	15
10166	Pt. Can with Applicator Cap	107250931	012181-101667	0.42	12	14
10165	Qt. Can with Applicator Cap	107250921	012181-101650	0.78	12	27
10164	Gal. Can with Screw-on Cap	107250911	012181-101643	1.21	6	53

738™ PVC HOT 'N FAST™ Blue, Medium-Bodied, Very Fast-Setting



- Low-VOC PVC cement for all classes and schedules with interference fit through 6" (160 mm) diameter, Schedule 80 through 4" (110 mm) diameter
- High-strength and very fast-setting speed make this cement ideal for irrigation, agriculture, pool and plumbing applications

- Blue fades to clear in sunlight
- For wet or quick pressurization conditions
- Can be used without primer on non-pressure systems if local codes permit



Product Code	Product Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
12248	½ Pt. Can with Applicator Cap	127370941	012181-122488	0.37	24	15
12247	Pt. Can with Applicator Cap	127370931	012181-122471	0.36	12	14
12246	Qt. Can with Applicator Cap	127370921	012181-122464	0.67	12	28
12245	Gal. Can with Screw-on Cap	127370911	012181-122457	1.07	6	53