


Fuse holder terminal blocks


Double deck for 5x20 and 5 x 25mm fuses

Screw clamp, DIN 1 - DIN3



D 4/8.D2.P.SF

Characteristics		IEC		UL	CSA
		NFC	DIN		
Wire size mm ² / AWG	Comp. clamp	Solid	0.5 - 6 mm ²	20-10 AWG	20-10 AWG
	feed through	Stranded	0.5 - 4 mm ²	20-12 AWG	20-12 AWG
	Comp. clamp ground	Solid	0.2 - 4 mm ²	20-10 AWG	20-10 AWG
		Stranded	0.22 - 4 mm ²	20-12 AWG	20-12 AWG
Voltage	V	300 ①	300 ②	300 ②	
Current	A	6.3	6.3	6.3	
Rated wire size	mm ² / AWG	4 mm ²	12 AWG	12 AWG	
Wire stripping length	mm / inches	9,5 mm / .37"			
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in			




Selection

Description	Type	Packaging	Catalog number
Grey	D 4/8.D2.P.SF	25	040027020
Grey Neon 110-230 V	D 4/8.D2.P.SFL	25	040027115
Grey LED 24 V	D 4/8.D2.P.SFD	25	040027216

Accessories

Description	Type	Packaging	Catalog number
1 End section grey V0	FEM8D2S 1.5 mm	20	040027317
2 Test socket	AL2 ② DIA. 2mm	50	016304321
	AL3 ② DIA. 3mm	50	016326100
	AL4 ② DIA. 4mm	50	016326201
3 Test plug	FC2 DIA. 2mm	100	000786526
	FC4 DIA. 4mm	10	016786001
4 Assembled jumper bar (without IP20 protection)	2 poles BJM8 ② 41 A	10	016852005
	3 poles BJM8 ② 41 A	10	016852122
	4 poles BJM8 ② 41 A	10	016852223
	5 poles BJM8 ② 41 A	10	016852324
	10 poles BJM8 ② 41 A	10	016897400
5 Connector plate	EL6 35 A	10	017352721
6 Comb-type jumper bar	PC81 35 A	10	017352311
7 IDC jumper	AD2,5 24 A	50	011420520
8 Assembly rod	2 poles TGA8	10	016867211
	3 poles TGA8	10	016867312
	4 poles TGA8	10	016867413
9 Assembly ring	ANT	10	016867514
10 Fuse 5 x 20	250 V FU520 0,5 A	10	000828815
	250 V FU520 1 A	10	000829013
	250 V FU520 2 A	10	000829100
	250 V FU520 3,15 A	10	000828916
	250 V FU520 5 A	10	000829201
	Fuse 5 x 25	250 V FU525 1,6 A	10
Fast acting HPC 1500 A	250 V FU525 2 A	10	016754723
	250 V FU525 2,5 A	10	016754804
	250 V FU525 4 A	10	016754905
	250 V FU525 6,3 A	10	016755002
	11 Disconnect link bar	CN5	10



① Insulation voltage of terminal block - operating voltage : according to fuse.
 ② Only for lower deck.