




## Specifications of Round Instant Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	12V	30'	4'	3.0V 0.07A 0.21W	12	2.52W/foot
	24V	60'	8'	3.0V 0.07A 0.21W	12	2.52W/foot
	110-120V	240'	24'	6.5V 0.07A 0.46W	12	3W/foot

## Packages Available

Item Number	Length	Package
ERIF-120-150	150'	/Roll
ERIF-24-150*	150'	/Roll
ERIF-12-150**	150'	/Roll

**ERIF - 120 - 150 - COLOR**

Item No.                      Voltage                      Length                      Specify color

(Available in 150' Rolls only, no custom cut)

NOTE: EACH ROLL INCLUDES; 3pcs ERIFXXX Power Cords, 3pcs F3 Splice Connectors, 3pcs F4 End Caps

## Round Instant Flexilight Accessories:

- ERIF1-120V    Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- ERIF1-24V\*    Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- ERIF1-12V\*\*    Round Instant Flexilight 6ft. Power Cord w/ Power Connector
- F3    Round Instant Flexilight Splice Connector
- F4    Round Instant Flexilight End Caps
- F5    Round Instant Flexilight Tie Strap
- F6    Round Instant Flexilight Mounting Clips
- F7    Round Instant Flexilight Suction Cup
- F8    Round Instant Flexilight 6ft. Channel
- F9    Round Instant Flexilight Easy Splice Connector
- F10    Round Instant Flexilight Y-cord
- F11    Round Instant Flexilight T-connector
- F14    Round Instant Flexilight Splice Connector
- F103    Round Instant Flexilight PVC Connector
- F22    Round Instant Flexilight PVC T-Connector
- F23    Round Instant Flexilight PVC X-Connector

ERIFI



F3



F4



F5



F6



F7



F8



F9



F10



F11



F14



F22



F23



F103



## Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-110	120V	150 FT.	Static/Flashing
ERWL-2C-24A*	24V	60 FT.	Static/Flashing
ERWL-2C-12A**	12V	30 FT.	Static/Flashing

(\*Requires 24V AC power source)

(\*\*Requires 12V AC power source)

