

MTW



Features extra flexible 30 AWG stranding. Rated as ASTM Class Flexing Service by NFPA 79 electrical standard for industrial machinery. Insulations, oil, moisture, and acid resistant. Approvals: NFPA 79 Electrical Standard for Industrial Machinery, NFPA 70 National Electric Code, UL1063 Machine Tool Wires and Cables, UL Subject 758 Appliance Wire and Material, CSA C22.2 No. 127 Equipment Wires, CSA C22.2 No 210.1 Appliance Wiring Material Products, ASTM B174 Bunch Stranded Copper Conductors.



41103

CAT NO	WIRE GAUGE	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
41101-05-xx	18	16/30	0.108	500	2000	22
41102-05-xx	16	26/30	0.120	500	2000	30
41103-05-xx	14	41/30	0.136	500	2000	40
41104-05-xx	12	65/30	0.155	500	2000	58
41105-05-xx	10	104/30	0.179	500	500	22
41109-05-xx	8	19/.0295	0.244	500	500	39
41110-05-xx	6	19/.0372	0.314	500	500	60

Color code: xx = White (01); Yellow (02); Orange (03); Red (04); Green (05); Blue (06); Brown (07); Black (08)

Yellow, Orange, Blue, Brown not available on 6 & 8 gauge.

2500' reels available on 18-10 gauge. Replace Put-up code -05 with -09. For example 12 gauge red on 2500' reel is 41104-09-04

Additional lengths and colors may be available. Please consult factory.

TFFN/TFN



PVC/Nylon insulated, 600V rated wire. AWM style 1316 and 1408. Rated gasoline and oil resistant.



51791

CAT NO	DESCRIPTION	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
51011-05-xx	18 AWG TFFN	16/30	.088	500	2000	18
51012-05-xx	16 AWG TFFN	16/30	.100	500	2000	26
51791-05-xx	18 AWG TFN	Solid	.082	500	2000	18
51792-05-xx	16 AWG TFN	Solid	.093	500	2000	24

Color code: xx = White (01); Yellow (02); Orange (03); Red (04); Green (05); Blue (06); Brown (07); Black (08)

2500' reels available on most colors. Replace Put-up code -05 with -09. For example 18 gauge red TFN on 2500' reel is 51791-09-04

Additional lengths and colors may be available. Please consult factory.

THHN



PVC/Nylon insulated, 600V rated wire. AWM style 1316 and 1408. Rated gasoline and oil resistant.



51041

CAT NO	GAUGE	STRANDING	OVERALL O.D.	SPOOL LENGTH (FT)	MASTER PK QTY (FT)	MASTER WT
51041-05-xx	14	Solid	.106	500	2000	36
51042-05-xx	12	Solid	.123	500	2000	52

Color code: xx = White (01); Red (04); Green (05); Blue (06); Black (08)

Additional lengths and colors may be available. Please consult factory.