



**MODEL NUMBER:** 076058800

**DESCRIPTION:** 400W MH LIGHT FX PS

**LISTINGS:** UL/CUL Listed; EISA200

**FEATURES & BENEFITS**

Energy Efficient and Long Life 400W Metal Halide Bulb  
 Quick installation with spring-loaded hanger  
 Heavy gauge steel guards to resist damage.  
 Quad-tap ballast (120v, 208v, 240v, 277v)

**CONSTRUCTION**

Dimensions: Approx. 10" diameter x 23" high, including mounting hood  
 Weight: 17 lbs (approx)  
 Housing: Steel, powder coated  
 Lamp guard: Plated steel wire, includes snap-on protective bottom guard  
 Ballast type: ANSI M155, pulse start  
 Capacitor: 26µF, 330VAC, 100oC  
 Lamp holder: EX39 exclusionary mogul base  
 Electrical supply: Supplied pre-wired with a 3.5' 18/3 SJTW power supply  
 Voltage options: Quad-tap ballast for operation at 120V (3.8A), 208V (1.9A), 240V (1.67A), 277V (1.5A)  
 Wiring options: (2) 1/2" knock-outs in wiring compartment accommodate 12-14 AWG wire  
 Lamp bulb (one included):  
 Lamp bulb wattage: 400 watts  
 Rated average bulb life: Over 10,000 hours  
 Bulb color temperature: 4000K  
 Lamp bulb type: Pulse start MP400, w/ extended eyelet mogul base, "E" type  
 Replacement bulb: CCI catalog number 07625 or equivalent



**TECHNICAL SPECIFICATIONS**

Operating temperature rating:  
 Operating environment: -40 to +60 C  
 Nominal operating voltage: 125, 208, 240, 277VAC  
 Nominal operating current: 120V (3.8A), 208V (2.2A), 240V (1.9A), 277V (1.5A)  
 Nominal operating wattage: 400W

**ORDERING INFORMATION**

UPC: 029892509538      Carton qty: 1  
 Carton dimensions: 17x11.75x15 inches  
 Carton weight: 20.85 lbs

**WARRANTY:** 1 Year Limited Warranty

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without

guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company, LLC.

**Southwire Company, LLC One Southwire Drive Carrollton, GA 30119 1-800-561-4321 [www.southwire.com](http://www.southwire.com)**

TYPE O

7 compliant with 88% energy efficiency