


Trac Sections



Catalog #	Finish	Description
R2WH	White	2' Trac
R2BL	Black	19 7/8" actual length
R2NA	Natural	
R2SL	Silver	
R2BZ	Bronze	
R4WH	White	4' Trac
R4BL	Black	43 7/8" actual length
R4NA	Natural	
R4SL	Silver	
R4BZ	Bronze	
R6WH	White	6' Trac
R6BL	Black	67 7/8" actual length
R6NA	Natural	
R6SL	Silver	
R6BZ	Bronze	
R8WH	White	8' Trac
R8BL	Black	91 7/8" actual length
R8NA	Natural	
R8SL	Silver	
R8BZ	Bronze	



Features

- Low 1/2" profile fits snugly to ceiling
- Rigid extruded aluminum channel
- Standard solid 12 gauge copper conductors
- 20 Amp capacity
- Debossed polarity line provides visual alignment with fixture and connector polarity arrows
- One circuit only
- Dead end and mounting hardware included
- Can be cut to custom length by installer

Trac Dead End



Trac Dead End

Catalog #	Finish	Description
R28WH	White	<ul style="list-style-type: none"> • Only required when terminating extra field cut-off sections • One supplied with Trac Section
R28BL	Black	
R28SL	Silver	
R28BZ	Bronze	




Electrical Feeds



End Feed Connector and Outlet Box Cover

Catalog #	Finish	Description
R21WH	White	<ul style="list-style-type: none"> • For outlet box feed • Includes outlet box cover, fixture strap, and ground screw
R21BL	Black	
R21SL	Silver	
R21BZ	Bronze	
R21RWH	White	<ul style="list-style-type: none"> • Same as above except designed for use in opposite polarity orientation compared to standard feed connectors • See specification sheets for more details
R21RBL	Black	
R21RSL	Silver	
R21RBZ	Bronze	



End Feed Connector

Catalog #	Finish	Description
R38WH	White	<ul style="list-style-type: none"> • Feeds Trac from above with Flex or BX • Accepts standard 1/2" electrical connector
R38BL	Black	
R38SL	Silver	
R38BZ	Bronze	
R38RWH	White	<ul style="list-style-type: none"> • Same as above except designed for use in opposite polarity orientation compared to standard feed connectors • See specification sheets for more details
R38RBL	Black	
R38RSL	Silver	
R38RBZ	Bronze	

