


CE 40 is now improved with two added clamping edges for greater holding power. Multiple uses include clamping for bends and turns and attachment that needs to span two wires in Cablofil tray.

FEATURES

- Use for splicing Cablofil tray on bends and adjustable turns
- Two CE 40's and one EZBN ¼ are required for each connection
- EZBN ¼ is sold separately
- UL Classified Splice



	PKG. QTY.	WEIGHT		EZ	GC	DC	316L	BL	PE
		LBS	KG						
CE 40	25	2.7	1.2	558 051	942 461	558 053	558 054	941 276	934 030

FINISHES		
SYMBOL	MATERIAL	FINISH & STANDARD
EZ	Carbon Steel	Electrozinc: Electrozinc plating ASTM B 633
GC	Carbon Steel ASTM A510 Grade 1008	Hot Dipped Galvanized: After Fabrication ASTM A 123
DC	Carbon Steel ASTM A510 Grade 1008	Geomet: Zinc and Aluminum Protection / Equivalent to Hot Dip Galvanization / ASTM F 1136
316L	Stainless Steel AISI Type 316L	Stainless Steel 316L: Cleaned and Passivated ASTM A 380
BL	Carbon Steel ASTM A510 Grade 1008	Black Painted: Black Powder Coated ASTM D 3451
PE	Carbon Steel ASTM A510 Grade 1008	Custom Painted: Custom Color Powder Coated ASTM D 3451

Legrand/Cablofil
 8319 State Route 4
 Mascoutah, IL 62258 USA
 1-800-658-4641
 618-566-3230
 Fax 618-566-3250
www.legrand.us/cablofil