

SNAP-TITE® Connectors

With spring steel clip. For NM • SE • MCI • MCIA • Flex • AC cable. For steel and aluminum jacketed cables. Zinc die-cast.

(See page E-1 for ring removal instructions.)



840ST



8400ST

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|
| 840ST | 80070 | 3/8 | 1/2 | 100 | 1000 | .485 | .879 | .858 | .225 - .610 |
| 8400ST | 80074 | 3/8 | 1/2 | 100 | 1000 | .485 | .879 | .858 | .225 - .610 |

SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information, see page 7.


Refer to pages C-13 and C-14 for complete cable ranges.

For connectors that cost less and install faster, see page C-8.

PATENTED




E28474 LR49636



840ST

8400ST



NM Cable Connector

For NM cable. Zinc die-cast.




| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|
| 841 | 00841 | 3/8 | 1/2 | 100 | 1000 | .422 | .825 | 1.105 | .225 - .612 |

Refer to pages C-13 and C-14 for complete cable ranges.

For connectors that cost less and install faster, see page C-8



E28474 LR49636



SNAP-TITE® Connector

With spring steel clip. For NM cable. Zinc die-cast.

(See page E-1 for ring removal instructions.)



| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|
| 841ST | 80068 | 3/8 | 1/2 | 100 | 1000 | .510 | .912 | .920 | .225 - .612 |

SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information, see page 7.

Refer to pages C-13 and C-14 for complete cable ranges.

PATENTED.



E28474 LR49636

