

## .300" Head Drive Pins with Top Hat

### PRODUCT DESCRIPTION

These pins are used primarily for applications fastening drywall track to concrete or steel. Pins are assembled with a metal top hat to provide faster insertion into the driving tool with reduced possibility of pricking a finger during load and to provide extra bearing surface against the drywall track.

### FASTENERS SIZES

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50136	1/2" (K)	0.145"	100	5,000	0.6
50138	5/8" (K)	0.145"	100	5,000	0.7
50140	3/4"	0.145"	100	5,000	0.7
50144	1"	0.145"	100	5,000	0.8

(K) = knurled



## .300" Head Drive Pins with Washers

### PRODUCT DESCRIPTION

To provide resistance to pullover, these pins are available with preassembled 14 gage (0.075") metal washers in various diameters. Resistance to pullover is increased by the additional bearing surface provided by the washer. The insulation washer has a thickness of 0.035".

### FASTENERS SIZES

#### .300" Head Drive Pins with 3/4" Washer

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50070	3/4"	0.145"	100	1,000	1.5
50080	2 1/2"	0.145"	100	1,000	2.5



#### .300" Head Drive Pins with 7/8" Washer

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50090	1"	0.145"	100	1,000	2.0
50092	1 1/4"	0.145"	100	1,000	2.1
50094	1 1/2"	0.145"	100	1,000	2.2
50096	2"	0.145"	100	1,000	2.5
50098	2 1/2"	0.145"	100	1,000	2.7
50100	3"	0.145"	100	1,000	3.3



#### .300" Head Drive Pins with 1" Washer

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50108	1 1/4"	0.145"	100	1,000	2.5
50110	1 1/2"	0.145"	100	1,000	2.6
50112	2"	0.145"	100	1,000	2.9
50114	2 1/2"	0.145"	100	1,000	3.3
50116	3"	0.145"	100	1,000	3.6



#### .300" Head Drive Pins with 1 7/16" Insulation Washer

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50122	1 1/2"	0.145"	100	1,000	2.5
50126	2 1/2"	0.145"	50	500	3.2



POWDER  
ACTUATED