

596-00247

Article Number: 596-00247

Pre-Printed Reflective Solar Label, 6.5" X 1", CAUTION: SOLAR CIRCUIT, Red, 50/pkg

CAUTION: SOLAR CIRCUIT



Base Data

Local Order Number 596-00247

Type CSCIRLBL

Color Red (RD)

Features and Benefits

- Pre-Printed Signal Word labels come with the header pre-printed in colors so that only one color of ribbon is needed to complete the message panel.
- Labels are pre-made to the most recent ANSI standards so that code compliance is assured.
- Pre-Printed Signal Panel labels can be printed using standard thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand when needed.

Color of Print White (WH)

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 6.5" X 1" White text on a red background that reads as: "CAUTION - SOLAR CIRCUIT" in 3/8" tall characters using reflective inks. 50 per pkg.

Short Description Pre-Printed Reflective Solar Label, 6.5" X 1", CAUTION: SOLAR CIRCUIT, Red, 50/pkg

Product Dimensions

Length L (imperial) 4.0 "

Length L (metric) 101.6 mm

Width W (imperial) 6.5 "

Width W (metric) 165.1 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Logistics and Packaging

Quantity per roll

Package Quantity (imperial) 50

Package Quantity 50

Labels per Column 1

Labels per Row 1

Weight (imperial) 31.97 oz

Material and Specifications

Material Vinyl

Material Shortcut Vinyl

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +302 °F (-40 °C to +150 °C)

Halogenfree Yes

Operating Temperature -40 °F to +180 °F (-40 °C to +82 °C)

ROHS Conformity Yes

UL Recognized (US) Yes