

THREADING

Cutting Oil



Thread Cutting Oil

- Cools threads and pipe during operation.
- Speeds metal removal.
- Improves thread quality.
- Reduces threading torque.

RIDGID® thread cutting oils are free of chlorine and other halogens, PCBs and heavy metals. Complete material safety data sheet available.

Selection

Feature	Dark	Nu-Clear	Endura-Clear	Extreme Performance
Low Odor	X	X	X	X
Anti-Mist Formulation	X	X	X	
Extended Die Life			X	X
FBC™ System Compatible**			X	
Designed for Stainless Steel				X
Working Viscosity	0°F	-20°	-20°	0°

Container Size		Catalog No.				Containers Per Case	Weight Per Case	
U.S.	Metric	Dark	Nu-Clear	Endura-Clear	Extreme Performance		lb.	kg
1 Qt.*	0.94 L	41590	–	–	–	12	22	10
1 Gal.	3.78 L	70830	70835	32808	74012	6	50	22,7
5 Gal.	18.90 L	41600	41575	–	74047	1	42	19
55-Gal.	207.90 L	41610	41585	–	76767	1	465	211
16 oz***	0.38 L	–	–	–	22088	12	12	5,5

*Flip top included with every quart bottle. ***Aerosol can.

**FBC™ System Compatible indicates that this product has been tested and is monitored on an ongoing basis to assure chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

FlowGuard Gold®, BlazeMaster®, Corzan® and FBC™ are trademarks of The Lubrizol Corporation. FBC™ is a trademark of The Lubrizol Corporation.

Oiler



Model 418 Oiler

The Model 418 hand-held oiler is sturdier than ever before. The 418's pump assembly and heavy-duty reservoir are designed to increase productivity.

Pump Assembly

- 50% more oil per stroke than other hand-held oilers for longer die life.
- An ergonomic 2-finger trigger design that reduces user fatigue.
- Die cast, heavy-duty body with swivel nozzle with no exposed parts for longer life.

Heavy Duty Reservoir

- The Model 418 oiler features a fastenerless twist and lock drip pan that easily locks in place.
- The material withstands abrasion, is lighter than metal and does not rust.
- The reservoir will not crack or leak.
- Material is so strong that under normal use, no dents will form on impact or shape changes will occur over time. As a result, the drip pan will fit squarely on the reservoir time after time.
- Integral molded body eliminates leaks at the hose-reservoir connection.
- Convenient anti-slip grip design with integral hook for easy hanging.

Selection

Catalog No.	Model No.	Description	Weight	
			lb.	kg
10883	418	Hand operated oiler complete. Includes 1 gallon of premium thread cutting oil, reservoir with removeable chip tray, and 54" hose	20½	9,4
72342	402	Hand operated oiler with attachment for 1 gallon and 5 gallon containers and 54" hose	2½	1,2
72332	#4	Hand-operated oiler only	1¼	0,5
72327	#4	Hand-operated oiler with 54" hose and hose fittings	2¼	1,0