


Screw terminal blocks - Disconnect


PB502179



PB502178



PB502193



		NSYTRV42SC	NSYTRV42TB	NSYTRV42SCD			
Nominal c.s.a.		4 mm ²	4 mm ²	4 mm ²			
	Type of block	Disconnect (blade)	Disconnect (for carrier)	Disconnect - Double deck			
	Type of connection	1 pole - 1 x 1	1 pole - 1 x 1	2 pole - 1 x 1			
	Color	Grey	Grey	Grey			
Max. electric values (U _{max} , I _{max})		500 V, 20 A	400 V, 20 A	500 V, 38 A			
Dimensions (mm)							
	Length	57.8	57.8	69.9			
	Height	49.1	47.5	65			
	Width	6.2	6.2	6.2			
Cabling c.s.a. (mm ²)		4	4	4			
	Flexible cable	0.14 - 6	0.14 - 6	0.14 - 6			
	Solid cable	0.14 - 6	0.14 - 6	0.14 - 6			
Nominal electric values							
	IEC/EN 60947-7-1	500 V, 20 A	500 V, 20 A	500 V, 30 A			
	UL	600 V, 16 A, 26 - 10 AWG	600 V, 16 A, 26 - 10 AWG	300 V, 30 A, 26 - 10 AWG			
	CSA	600 V, 16 A, 26 - 10 AWG	600 V, 16 A, 26 - 10 AWG	300 V, 30 A, 26 - 10 AWG			
	ATEX	-	-	-			
Certifications		UL, CSA, GOST	UL, CSA, GOST	UL, CSA, GOST			
Terminal blocks							
		Sold in lots of	Unit reference	Sold in lots of	Unit reference	Sold in lots of	Unit reference
	Grey	50	NSYTRV42SC	50	NSYTRV42TB	50	NSYTRV42SCD
	Grey, with test points	50	NSYTRV42ST	-	-	-	-
	Orange, with test points	50	NSYTRV42STAR	-	-	-	-
Accessories							
End stop	Clip-on, 5.2 mm	50	NSYTRAAB35	50	NSYTRAAB35	50	NSYTRAAB35
for 35mm DIN rail	With screw, 9.5 mm	50	NSYTRAABV35	50	NSYTRAABV35	50	NSYTRAABV35
End plate,	Grey	-	Included	-	Included	50	NSYTRACE24
width 2.2 mm	Grey, partial plate	-	-	-	-	50	NSYTRACPE24
Partition plate,	Grey	50	NSYTRAP23	50	NSYTRAP23	50	NSYTRAPE24
width 2 mm	Blue	-	-	-	-	-	-
Plug-in bridge	2-pole	50	NSYTRAL42	50	NSYTRAL42	50	NSYTRAL42
Red	3-pole	50	NSYTRAL43	50	NSYTRAL43	50	NSYTRAL43
	4-pole	50	NSYTRAL44	50	NSYTRAL44	50	NSYTRAL44
	5-pole	50	NSYTRAL45	50	NSYTRAL45	50	NSYTRAL45
	10-pole	10	NSYTRAL410	10	NSYTRAL410	10	NSYTRAL410
	20-pole	10	NSYTRAL420	10	NSYTRAL420	10	NSYTRAL420
Vertical bridge	1-pole	-	-	-	-	-	-
Removable carrier	For fuse 5 x 20 mm	-	-	-	NSYTRASF520	-	-
	For fuse 5 x 20 mm 110 - 250 V LED	-	-	-	NSYTRASF520M	-	-
	For fuse 5 x 20 mm 12 - 30 V LED	-	-	-	NSYTRASF520B	-	-
	For component	-	-	-	NSYTRASV1	-	-
	With 1N4007 diode	-	-	-	NSYTRASV2	-	-
Test plug	Metalic part, Ø 2.3 mm	10	NSYTRAATM1	10	NSYTRAATM1	10	NSYTRAATM1
	Insulating sleeve, red	10	NSYTRAATP1	10	NSYTRAATP1	10	NSYTRAATP1
Test adaptor	For plug-in bridge shaft	10	NSYTRAFT	10	NSYTRAFT	10	NSYTRAFT
Warning label	Yellow	10	NSYTRACS4	10	NSYTRACS4	10	NSYTRACS4
Marker tag holder	For ●AB35 end stop	100	NSYTRASB4	100	NSYTRASB4	100	NSYTRASB4
DIN rail 35 x 7.2 mm	Perforated, 2 m long	20	NSYSDR200BD	20	NSYSDR200BD	20	NSYSDR200BD
Marking accessories		See page 126					
General data							
	Strip length (mm)	9	9	9	9	9	9
	Screw thread	M3	M3	M3	M3	M3	M3
	Torque (Nm)	0.6 - 0.8	0.6 - 0.8	0.6 - 0.8	0.6 - 0.8	0.6 - 0.8	0.6 - 0.8