



OUTRIGGER PADS

The Lightweight HEAVY DUTY Outrigger Pad!



**Many
Standard
Sizes**

Features...

- Safety textured
- Safety orange rope handles
- No splinters
- No warping
- No delamination
- Lightweight
- Recovery memory after bending



**Safety
Textured**

The only engineered, quantifiable and rated Outrigger pad available today.



AlturnaMats pads are engineered to bend but not break!

**“If you break it,
we’ll replace it”**

Lifetime Guarantee

Stock Outrigger Pads

Model	Load	Capacity	Width	Length	Height	Weight	Sq. In.
	Vertical	45° Angle					
PAD15151	45,000# (KG20,412)	20,000# (KG9,072)	15" (C38.1)	15" (C38.1)	1" (C2.54)	7.5# (KG3.40)	225 (CT1,451.70)
PAD18181	55,000# (KG24,948)	30,000# (KG13,608)	18" (C45.72)	18" (C345.72)	1" (C2.54)	11.0# (KG4.99)	324 (CT2,090.45)
PAD24241	60,000# (KG27,216)	35,000# (KG15,876)	24" (C60.96)	24" (C60.96)	1" (C2.54)	20.0# (KG9.07)	576 (CT3,761.35)
PAD24242	62,000# (KG28,123)	40,000# (KG18,144)	24" (C60.96)	24" (C60.96)	2" (C5.08)	38.0# (KG17.24)	576 (CT3,761.35)

Non-Stock Specialty Pads

PAD30301	81,000# (KG36,741)	41,000# (KG18,597.6)	30" (C76.2)	30" (C76.2)	1" (C2.54)	31.0# (KG14.06)	900 (CT5,806.8)
PAD36361	93,000# (KG42,184.8)	43,000# (KG19,504.8)	36" (C91.44)	36" (C91.44)	1" (C2.54)	45.0# (KG20.41)	1296 (CT8,361.79)
PAD48481	135,000# (KG61,236)	52,000# (KG23,587.2)	48" (C121.92)	48" (C121.92)	1" (C2.54)	80.0# (KG36.29)	2304 (CT14,865.4)
PAD30302	85,000# (KG38,556)	43,000# (KG19,504.8)	30" (C76.2)	30" (C76.2)	2" (C5.08)	62.0# (KG28.12)	900 (CT5,806.8)
PAD36362	98,000# (KG44,252.8)	45,000# (KG20,412)	36" (C91.44)	36" (C91.44)	2" (C5.08)	90.0# (KG40.83)	1296 (CT8,361.79)
PAD48482	140,000# (KG63,504)	55,000# (KG24,948)	48" (C121.92)	48" (C121.92)	2" (C5.08)	160.0# (KG72.58)	2304 (CT14,865.4)

*8"x10" Outrigger Leg applied under two separate conditions; 10,000# vertically and 10,000# with a 45 degree angle.
 **Rope Handle located on width side of all pads. Pads 900 sq.in. or larger have two or more handles opposite each other.
 Custom size pads available. Requires a minimum order. Lead time for non-stock items is 30-45 days.
 KEY: C = Centimeters; KG = Kilograms; CT = Square Centimeters

• NOTICE •

- Foot pads must be smooth and have 80 sq. in. of surface.
- Muddy or loose soil conditions may require additional shoring or stacking of pads.
- Excessive flexing and/or bending may shorten the usable life of the pad.
- Acceptable operating temperature range is -40° to 180°F.



**No More
Plywood**

sales@alturnamats.com

PO Box 344 • Titusville, PA 16354
 Toll Free: 888-544-6287 • Office: 814-827-8884
 Fax 814-827-2903 • Toll Free Fax: 866-723-2903