

PREMIUM 111

A 7 mil (0,18mm) all weather, professional grade, pressure sensitive vinyl tape which gives excellent performance over a wide range of temperatures. Cold and weather resistant. Can be used as primary insulation for splices at not more than 600 Volts. Use as protective outer jacket over splices and all low temperature applications. UL 510, ASTM-D-3005, HH-595C. Lead-free.

PLYWRAP® 11 (10 mil) Vinyl Pipewrap

A corrosion protection, pressure sensitive vinyl tape giving complete environmental, mechanical and electrical protection for all types of pipewrapping applications. UV, bacteria and fungus resistant, Plywrap 11 tape can be used for both overhead and direct burial applications. Fed. Spec. L-T-001512. Lead-free.

HD 2 (Heavy Duty Electrical Tape)

A 10 mil (0,25mm) heavy duty, general purpose, pressure sensitive vinyl tape for all types of mechanical and electrical applications. Allows for quicker build-ups and added abrasion protection. Is flame retardant and can be used as primary insulation for splices at not more than 600 volts., ASTM-D-2301, MIL-I-7798A. Lead-free.



VINYL ELECTRICAL TAPES

PREMIUM 111

Cat.	Color	Dimensions		Packaging	Weight
4444	black	2" x .007" x 20'	50mm x 0,18mm x 6m	125/case PC	23 lbs 10 kg
4452	black	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100/case C	24 lbs 11 kg
4453	black	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100/case PC	24 lbs 11 kg
4461	black	2" x .007" x 66'	50mm x 0,18mm x 20m	40/case C	23 lbs 10 kg

HD 2

Cat.	Color	Dimensions		Packaging	Weight
8724	black	2" x .010" x 108'	50mm x 0,25mm x 33m	40/case C	46 lbs 21 kg

PLYWRAP® 11 (10 mil)

Cat.	Color	Dimensions		Packaging	Weight
4610	black	1" x .010" x 100'	25mm x 0,25mm x 30m	48/case C	26 lbs 12 kg
4611	black	2" x .010" x 100'	50mm x 0,25mm x 30m	24/case C	26 lbs 12 kg
4601	black-Printed	2" x .010" x 100'	50mm x 0,25mm x 30m	24/case C	26 lbs 12 kg

Consult customer service for other available sizes & colors.

NEW UTILITY **85** **ASK FOR IT!**

NEW **PLYWRAP** **ALSO PRINTED** **ASK FOR IT!**