

**ORDERING INFORMATION**

**Steel Vertical Hanger (#3 for Purlins, #5 for Beams)**

Cat. No.	Rod Dia.	Screw Shank Size and Length	Point Style	Self Drilling Range	Std. Box	Std. Ctn.
7155	1/4"	1/4-20 x 1"	#3	0.036" (20 gage) to 0.188" (3/16")	100	500
7157	3/8"	1/4-20 x 2"	#3		100	500
7158	3/8"	1/4-20 x 1" (w/nut)	#3		100	500
7159	3/8"	1/4-20 x 1 1/2"	#3		100	500
7160	3/8"	1/4-20 x 1 1/2" (w/nut)	#3	0.188" (3/16") to 0.500" (1/2")	100	500
7152	1/4"	12-24 x 1 1/2"	#5		100	500
7154	3/8"	12-24 x 1 1/2" (w/nut)	#5		100	500
7161	1/2"	12-24 x 1 1/2" (w/nut)	#5		100	500



**Steel Side Hanger (#3 for Purlins, #5 for Beams)**

Cat. No.	Rod Dia.	Screw Shank Size and Length	Point Style	Self Drilling Range	Std. Box	Std. Ctn.
7183	1/4"	1/4-20 x 1"	#3	0.036" (20 gage) to 0.188" (3/16")	100	500
7184	3/8"	1/4-20 x 1" (w/nut)	#3		100	500
7186	3/8"	1/4-20 x 1 1/2"	#3		100	500
7188	3/8"	1/4-20 x 1 1/2" (w/nut)	#3		100	500
7200	1/4"	12-24 x 1 1/2"	#5	0.188" (3/16") to 0.500" (1/2")	100	500
7201	3/8"	12-24 x 1 1/2" (w/nut)	#5		100	100



**Wood Vertical Hanger**

Cat. No.	Rod Dia.	Screw Shank Size and Length	Point Style	Pre-Drill Diameter (If Required)	Std. Box	Std. Ctn.
7163	1/4"	1/4" x 2"	Type 17	1/8"	100	500
7203	3/8"	1/4" x 1"	Type 17		100	500
7165	3/8"	1/4" x 2"	Type 17		100	500
7167	3/8"	1/4" x 3"	Type 17		100	500
7169	3/8"	1/4" x 4"	Type 17		100	500
7162	3/8"	3/8" x 2 1/2"	Type 17		100	500
7164	1/2"	3/8" x 2 1/2"	Type 17		100	500



**Wood Side Hanger**

Cat. No.	Rod Dia.	Screw Shank Size and Length	Point Style	Pre-Drill Diameter (If Required)	Std. Box	Std. Ctn.
7185	1/4"	1/4" x 1"	Type 17	1/8"	100	500
7205	3/8"	1/4" x 1"	Type 17		100	500
7170	3/8"	1/4" x 2"	Type 17		100	500
7156	3/8"	3/8" x 2 1/2"	Type 17		100	500



**Concrete Vertical Hanger**

Cat. No.	Rod Dia.	Screw Shank Size and Length	Thread Style	Pre-Drill Diameter	Std. Box	Std. Ctn.
7171	1/4"	1/4" x 1 1/4"	Wedge-Bolt OT	1/4" ANSI	100	500
7173	3/8"	1/4" x 1 1/2"	Wedge-Bolt OT	1/4" ANSI	100	500
7175	1/2"	3/8" x 2 3/4"	Wedge-Bolt OT	3/8" ANSI	50	250

For side mount concrete applications use Catalog Number 7185 and 7170 with a 1/4" ANSI drill bit.



**Drive Sockets and Pole Tool**

Cat. No.	Description	RPM	Std. Box	Std. Ctn.
7166	6'-12' Pole Tool (includes three Jaw Chuck)	N/A	1	1
7187	Universal Steel & Wood Socket (Red)	500 to 1500 RPM	5	25
7195	1/4" Concrete Socket (Blue)	-	5	25
7197	3/8" Concrete Socket (Blue)	-	5	25
7198	1/2" Concrete Socket (Blue)	-	5	25



**Concrete Vertigo Installation Accessories**

Cat. No.	Description	Maximum Bit Length	Std. Box	Wt./Each
5865	Tapper 3000 Tool Kit — Hex Driver (used with Cat#5860) Sleeve Assembly (same as Cat# 5874) 1/4" and 3/8" Concrete Drive Sockets (Blue)	6"	1	3/4
5874	Sleeve Assembly	6"	1	-
Cat. No.	Description	Usable Length	Std. Tube	Wt./10
5860	1/4" x 4 1/2" Straight Shank Drill Bit	3"	5	1/2
5866	1/4" x 6" Hex Shank SDS Drill Bit	4"	1	1/2

