

**Accessories
EW 35**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | |
|------------|----------------------------|
| Type | EW 35 |
| Order No. | 0383560000 |
| Version | Accessories, End bracket |
| GTIN (EAN) | 4008190181314 |
| Qty. | 50 pc(s). |

Accessories
EW 35

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|--------|-----------------|------------|
| Width | 8.5 mm | Width (inches) | 0.335 inch |
| Height | 46 mm | Height (inches) | 1.811 inch |
| Depth | 27 mm | Depth (inches) | 1.063 inch |
| Net weight | 5.32 g | | |

Temperatures

| | | | |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

Material data

| | | | |
|---------------------------|--------------|--------|-------|
| Material | Polyamide 66 | Colour | Beige |
| UL 94 flammability rating | V-2 | | |

System specifications

| | | | |
|---------|-------------------|---------------|-------|
| Version | For the terminals | Mounting rail | TS 35 |
|---------|-------------------|---------------|-------|

Additional technical data

| | | | |
|---------------------|-----------------|-----------|------------------|
| Installation advice | Direct mounting | Interlock | for screw fixing |
| Type of mounting | Screwed | | |

Conductors for clamping (rated connection)

| | | | |
|-------------------------|--------|-------------------------|--------|
| Tightening torque, max. | 0.6 Nm | Tightening torque, min. | 0.5 Nm |
|-------------------------|--------|-------------------------|--------|

Dimensions

| | |
|--------------|---------|
| TS 35 offset | 22.5 mm |
|--------------|---------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001041 | ETIM 4.0 | EC001041 |
| ETIM 5.0 | EC001041 | ETIM 6.0 | EC001041 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-08-10-03 |
| eClass 6.2 | 27-08-10-03 | eClass 7.1 | 27-08-10-03 |
| eClass 8.1 | 27-14-11-35 | eClass 9.0 | 27-14-11-35 |
| eClass 9.1 | 27-14-11-35 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|-------------------------------------|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD |
| Engineering Data | 12723_EW_35_DXF.dxf |