

Marine Products  
**Ship-to-Shore Selection Chart - Boatside**

**30A  
 125V AC  
 2 Pole  
 3 Wire**

Pages Y-7 to Y-11



HBL303NM



HBL303SS



HBL26CM13



HBL60CM33  
 HBL60CM33W

**50A  
 125V AC  
 2 Pole  
 3 Wire**

Pages Y-12, Y-13, Y-16



HBL503NM



HBL503SS



HBL63CM60



HBL77CM15  
 HBL77CM15W

**50A  
 125/250V AC  
 3 Pole  
 4 Wire**

Pages Y-14 to Y-16



HBL504NM



HBL504SS



HBL63CM64



HBL77CM15  
 HBL77CM15W

**100A  
 125/250V AC  
 3 Pole  
 4 Wire**

Pages Y-17 to Y-19



M4100B12R



M4100C12R

**100A  
 3ØY  
 4 Pole  
 5 Wire**

Pages Y-17, Y-20, Y-21  
 120/208V AC  
 277/480V AC



M5100B9R  
 M5100B7R



M5100C9R  
 M5100C7R

**200A  
 600V AC/250V DC  
 50-400 Hertz  
 4 Pole  
 5 Wire**

Pages Y-22, Y-23



M5200BS1R



M5200CS1R

**Portable  
 Telephone  
 Cable TV  
 Devices**

Pages Y-30, Y-31



HBLPHTVNM



HBLPHTVSS



HBLTVSS



PH6624



PH7440

**Ship-to-Shore Devices**



**HBL26CM10**



**HBL26CM11**



**HBL60CM31**



**HBL26CM13**



**HBL60CM33**



**HBL60CM32**

**30A 125V Ship-to-Shore Devices**

| Description  | Catalog Number        |
|--|-----------------------|
| Yellow single receptacle has Rynite® body and abuse resistant nylon face.<br>IP20 SUITABILITY.   | <b>HBL26CM10</b>      |
| Yellow Insulgrip® plug has rugged nylon housing and cord grip with range of .36-.93 in. (9-24) that utilizes a unique offset jaws arrangement to provide secure strain relief.<br>IP20 SUITABILITY.  | <b>HBL26CM11</b>      |
| Yellow Seal-Tite® cover for weatherproofing HBL26CM11 plugs.<br>IP44 SUITABILITY. Note: Fits Insulgrip devices only.   | <b>HBL60CM31+</b>     |
| White Seal-Tite cover for weatherproofing HBL26CM11 plugs.<br>IP44 SUITABILITY. Note: Fits Insulgrip devices only.   | <b>HBL60CM31W+</b>    |
| Yellow Insulgrip connector body has rugged nylon housing and cord grip with range of .36-.93 in. (9-24) that utilizes a unique offset jaws arrangement to provide secure strain relief.  | <b>HBL26CM13</b>      |
| Yellow Seal-Tite cover for weatherproofing HBL26CM13 connector bodies when used with shore power inlets. Threaded sealing ring makes connection watertight. Also for weatherproofing HBL26CM11 plug when used with HBL303SSO power outlet.<br>IP56 SUITABILITY. Note: Fits Insulgrip devices only.                   | <b>HBL60CM33+</b>     |
| White Seal-Tite cover for weatherproofing HBL26CM13 connector body when used with shore power inlets. Threaded sealing ring makes connection watertight. Also for weatherproofing HBL26CM11 plug when used with HBL303SSO power outlet.<br>IP56 SUITABILITY. Note: Fits Insulgrip devices only.                      | <b>HBL60CM33W+</b>    |
| Yellow Seal-Tite cover for weatherproofing HBL26CM13 connector bodies when used on extension cords or adapters. IP44 SUITABILITY. Note: Fits Insulgrip devices only.   | <b>HBL60CM32+</b>     |
| Yellow polycarbonate spring-loaded lift cover for weather-proofing old style 26CM10 receptacle. Meets the most stringent requirements of UL's three listing categories for weatherproof plates. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. IP44 SUITABILITY. | <b>HBL74CM24WO**</b>  |
| Same as HBL74CM24WO except gray in color. IP44 SUITABILITY.  | <b>HBL7424WO**</b>    |
| Yellow polycarbonate spring-loaded lift cover for weather-proofing HBL26CM10 receptacle. Meets the most stringent requirements of UL's three listing categories for weatherproof plates. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. IP44 SUITABILITY.        | <b>HBL74CM25WOA**</b> |
| Same as HBL74CM25WOA except white in color. IP44 SUITABILITY.  | <b>HBL74CM25WOAW</b>  |
| Same as HBL74CM25WOA except gray in color. IP44 SUITABILITY.   | <b>HBL7425WOA**</b>   |
| Stainless steel wall plate for old 26CM10.   | <b>SS725</b>          |
| Stainless steel wall plate for new HBL26CM10.  | <b>SS720</b>          |

Note: \*\*See page Y-45 for accessories.  
 +Boots are not UL Listed.

Rynite® is a registered trademark of E. I. DuPont.