

Wallmount Accessories

General

Oiltight Hole Seals

Oiltight hole seals are used to seal unused or empty pushbutton holes, conduit openings, and knockout openings from the entry of dirt, dust, oil and water.

Material:

Carbon Steel:
RAL 7035 (light gray)
Stainless Steel: 304 & 316

Hole Seals:

- 12 sizes
- Covers holes with a 0.19" diameter

- Can be used on material thickness up to .31"
- Oil-resistant gasket
- UL/cUL Type 4/4X 12 and 13.

Oiltight Hole Seals - Carbon Steel

Description	Part No.
Miniature Oiltight Pushbutton Hole 22.5 mm (IEC)	OHSMPBC
0.50" Conduit Hole	OHS050C
0.75" Conduit Hole	OHS075C
Standard Oiltight Pushbutton Hole 30.5 mm (NEMA)	OHSSPBC
1.00" Conduit Hole	OHS100C
1.25" Conduit Hole	OHS125C
1.50" Conduit Hole	OHS150C
1.75" Conduit Hole	OHS175C
2.00" Conduit Hole	OHS200C
2.50" Conduit Hole	OHS250C
3.00" Conduit Hole	OHS300C
3.50" Conduit Hole	OHS350C
4.00" Conduit Hole	OHS400C

Oiltight Hole Seals - Stainless Steel 316L

Description	Part No.
Miniature Oiltight Pushbutton Hole 22.5 mm (IEC)	OHSPB6
0.50" Conduit Hole	OHS0506
0.75" Conduit Hole	OHS0756
Standard Oiltight Pushbutton Hole 30.5 mm (NEMA)	OHSSPB6
1.00" Conduit Hole	OHS1006
1.25" Conduit Hole	OHS1256
1.50" Conduit Hole	OHS1506
1.75" Conduit Hole	OHS1756
2.00" Conduit Hole	OHS2006
2.50" Conduit Hole	OHS2506
3.00" Conduit Hole	OHS3006
3.50" Conduit Hole	OHS3506
4.00" Conduit Hole	OHS4006

See page 153-157 for Pushbutton Enclosures