

U7021-RL-TG-KK-BLG



4 Terminal Ringless Small Hub Open Triplex Ground Horn Bypass
 7-8 In Barrel Lock Ground With Bracket Provision 200 Ampere

SPECIFICATIONS

Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.125L x 8W x15.5H
Number of Main Breakers	0
Main Breaker Size	No Main Breaker
Cable Entry	Overhead
Terminal	Lay in



Insulation	Glass Polyester
Mounting	Surface Mount
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	4 Terminal
Bypass Provision	Horn Bypass
Number of Meter Positions	1 Position
Equipment Ground	Triplex Ground
Hub/Closing Plate	Small Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Barrel Lock Provision	7/8 Inch Knockout and Angle Bracket For Barrel Lock Provision
Number of Receptacles	0
Height	15.5 IN
Length	4.125 IN
Width	8 IN

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by