

VX475, VX550 AND VX1000 POWER UNITS SELECTION CHART

| | 2-Year Warranty | | 4-Year Warranty | | 8-Year Warranty | |
|--|-----------------|--------|-----------------|--------|-----------------|---------|
| | VX475 | VX475C | VX550 | VX550C | VX1000 | VX1000C |
| Motor Performance Power (Air Watts) | 475 | 475 | 550 | 550 | 1040 | 1040 |
| Current Rating (Amps) | 15 | 15 | 15 | 15 | 15 | 15 |
| Voltage | 120 | 120 | 120 | 120 | 240 | 240 |
| Recommended Circuit (Amps) | 20 | 20 | 20 | 20 | 20 | 20 |
| Bag required for debris recovery | • | | • | | • | |
| Cyclonic bagless debris recovery | | • | | • | | • |
| On/Off Indicator | • | • | • | • | • | • |
| Easy access door for convenient & cleaner dirt removal | • | • | • | • | • | • |
| Easy access door for maintenance of cyclonic filter | | • | | • | | • |
| Easy-to-use bag change mechanism allows for simple & fast bag changing | • | | • | | • | |
| Easy-to-use bag change mechanism closes bag reducing loose dust & dirt | | | • | | • | |
| Filter Bag Capacity (Gallons) | 6 | | 8 | | 8 | |
| "Bag Full" indicator with progressive fill indication | | | • | | • | |
| Debris Pail Capacity (Gallons) | | 4 | | 7 | | 7 |
| "Pail Full" indicator with progressive fill indication | | | | • | | • |
| HEPA® media with anti-stick technology | | | • | • | • | • |
| Unique oval shape for efficient cyclonic filtration | | • | | • | | • |
| Built-in sound suppression system | • | • | • | • | • | • |
| For homes up to: | | | | | | |
| 4,000 square feet | • | • | | | | |
| 8,000 square feet | | | • | • | | |
| 12,000 square feet | | | | | • | • |

Dimensions: 475 Model 36 x 16.5 x 11.5, 550 and 1000 Models 39 x 17.5 x 11.5

Tubings



3808

NuTone's semi-rigid white PVC tubing has exceptional tensile strength. Lightweight and easy to handle, it can be cut with an ordinary saw. Its self-extinguishing properties will not support combustion making it extremely safe for your home's walls. Installs vertically or horizontally and is not affected by weather – won't rust or deteriorate.

- Conforms to all UL requirements
- Manufactured in conformity with ASTM F2158
- 2" OD x 8'; eight pieces – 64 feet

Tubing Guide

| Number of Inlets | 3 | 4 | 5 | 6 | 7 |
|---------------------|-----|-----|-----|------|------|
| PVC Tubing Required | 48' | 64' | 80' | 100' | 120' |

Fittings, tubing and installation kits to meet every installation need – all from one source... NuTone.

Bulk packs available! Please check NuTone price sheet or packaging information.