

Product data sheet

Characteristics

SDSA1175

Surge Protect - 36kA - 120/240VAC - 1P3W - T4X

Product availability : Stock - Normally stocked in distribution facility



Price* : 95.68 USD



Main

Product	Surge protection device
Range	Square D

Complementary

Surge Current	36 kA per phase
System Voltage	120/240 V AC
Phase	1 phase
Wiring Configuration	3-wire
MCOV	150 V
Nominal Discharge Current	10 kA
SCCR	25 kA
Local Signalling	Status LED, green = normal operation
Height	2.25 in
Width	2.25 in
Depth	2.7 in

Environment

Enclosure Rating	NEMA 4X
Enclosure Material	Plastic, colour : black
Standards	NEC 285 CSA C22.2 No 8 UL 1449 type I ed. 4
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B

GTIN	00785901210870
Nbr. of units in pkg.	20
Package weight(Lbs)	0.70000000000000007
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------