

**Protective Boots for Type K and SK Operators**

**Table 19.294: Protective Boots**




| For Non-Illuminated Push Buttons [152] |            | Clear Color for  | Type [153] |
|--|------------|--|------------|
| Color                                  | Type [153] |  |            |
| Black                                  | KU1        | Standard knob selector switch                            | KU17       |
| Red                                    | KU2        |  |            |
| Blue                                   | KU3        |  |            |
| Brown                                  | KU4        | Gloved-hand cap for use on standard knob selector switch | KU18       |
| Green                                  | KU5        |  |            |
| Yellow                                 | KU6        | Standard pilot light and maintained contact push buttons | KU27       |
| Clear                                  | KU7        |  |            |
| Clear                                  | KU8        |  |            |
| (Provides Full Guard)                  |            | Illuminated push button with guard                       | KU47       |

**NOTE:** These Type KU protective boots are recommended for very dirty environments or severe hose down, but they are not required for UL Type 4 rating on the Type K operators or UL Type 4 or 4X rating on the Type SK operators. The K1 wrench (see [Wrenches for Type K and SK Operators, page 19-101](#)) is required for installation of these boots.

**Closing Plates for Type K and SK Operators**

**Table 19.295: Closing Plates**

| <br>Round (1-1/2 in. Dia.) | Description | Type      |
|---|-------------|-----------|
|   | Gray        | K51 [154] |
| Black   | K52 [154]   |           |

For Dimensions, see catalog 9001CT0001

[152] Use KU27 for maintained contact push buttons.  
[153] When ordering, add prefix 9001 to the catalog number.  
[154] Meets UL and NEMA 1, 2, 3, 4, 4X, 6, 12 and 13.