



Protected LED™

Table 19.165: Body/Mounting Collar

For use with	Catalog Number
Electrical block (contact or light module)	ZB5AZ009

Table 19.166: Add-On Contact Block (with screw clamp terminal connections) [68]

[69]

Description	Type of Contact		Catalog Number
	N.O.	N.C.	
Standard single contact blocks [70][71]	1	—	ZBE101
	—	1	ZBE102
Standard double contact blocks [70][71]	2	—	ZBE203
	—	2	ZBE204
	1	1	ZBE205
Special contact blocks for low-power switching [72]	1	—	ZBE1016
	—	1	ZBE1026
Low-power switching	1	—	ZBE1016P
	—	1	ZBE1026P
Staggered contacts	1	—	ZBE201
	—	1	ZBE202
	1	1	ZB4BZ106
	—	2	ZB4BZ107

Table 19.167: Light Modules (with screw clamp terminal connections) [68][69]

Description	Supply Voltage	Color of Light Source	Catalog Number
	12 Vac/Vdc	White	ZBVJ1
		Green	ZBVJ3
		Red	ZBVJ4
		Yellow	ZBVJ5
		Blue	ZBVJ6
		24 Vac/Vdc	White
Green	ZBVB3		
Red	ZBVB4		
Yellow	ZBVB5		
Blue	ZBVB6		
110–120 Vac	White		ZBVG1
	Green	ZBVG3	
	Red	ZBVG4	
	Yellow	ZBVG5	
	Blue	ZBVG6	
	24–120 Vac/Vdc	White	ZBVBG1
Green		ZBVBG3	
Red		ZBVBG4	
Yellow		ZBVBG5	
Blue		ZBVBG6	
230–240 Vac		White	ZBVM1
	Green	ZBVM3	
	Red	ZBVM4	
	Yellow	ZBVM5	
	Blue	ZBVM6	
	Direct supply for BA9s (2.4 W max. bulb not included—see Table 19.183 BA9s Bulbs and Associated Accessories, page 19-61)	< 250 Vac/Vdc	—

[68] Electrical components with connection by printed circuit board pins are available. Refer to Catalog [9001CT0001](#) for more details.

[69] Electrical components with connection by plug-in connector are available. Refer to Catalog [9001CT0001](#) for more details.

[70] For Quick-Connect version add "3" to the end of the catalog number (Example: ZBE1013) (Quick-Connect size 1 x 0.250" or 2 x 0.110").

[71] For Ring Tongue compatible blocks add "9" to the end of the catalog number (Example: ZBE1029).

[72] Cannot stack additional contact blocks onto these blocks.