

CONTROLS AND ACCESSORIES

COMMERCIAL PIPE TRACING CONTROLS

Intended for temperature control of a variety of electric heating cables and applications, EasyHeat's commercial pipe tracing controls are UL Listed and CSA Certified. See item specific certifications below.

C3RC Thermostat – The C3RC thermostat is suitable for indoor/outdoor locations and is used with pipe freeze protection, pipe tracing or roof and gutter de-icing heating cable applications. This thermostat has a rainproof, gasketed enclosure that can be used in an ambient-sensing mode (with capillary coiled, as received) or a line sensing mode (with capillary attached to pipe).

C4XC Thermostat – The C4XC thermostat is suitable for indoor/outdoor locations having hostile, non-hazardous environments. This thermostat controls freeze-protection pipe tracing or roof and gutter de-icing heating cable applications. The C4XC can be used in an ambient-sensing mode (with capillary coiled, as received) or a line sensing mode (with capillary attached to pipe).







T4XC Thermostat – The T4XC thermostat is intended to control temperature-maintenance pipe tracing applications. The T4XC is suitable for indoor/outdoor locations having hostile, non-hazardous environments.

T4XA Thermostat – The T4XA thermostat is suitable for indoor/outdoor locations having hostile, non-hazardous environments and controls a variety of electric heating cables for freeze-protection pipe tracing or roof and gutter de-icing.




T9EC Thermostat – The T9EC thermostat is intended for temperature-maintenance pipe tracing applications. The T9EC is suitable for indoor/outdoor hazardous locations having hostile environments.

T9EA Thermostat – The T9EA thermostat is intended for temperature control of electric heating cables for freeze-protection pipe tracing. The T9EA is suitable for indoor/outdoor hazardous locations having hostile environments.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
C3RC	SPDT, snap action thermostat, 22 Amp, 0°-150°F/-18°-66°C, 6° diff., 10 ft capillary, NEMA 3R enclosure	1	2.7	0-13627-01327-8	
C4XC	SPST, snap action thermostat, 22 Amp, 40°F/4°C fixed, 3° diff., 5-6 ft capillary, NEMA 4X enclosure	1	2	0-13627-01328-5	
T4XC	SPDT, snap action thermostat, 22 Amp, 25°-325°F/-4°-163°C, 6° diff., 10 ft capillary, NEMA 4X enclosure	1	4	–	
T4XA	NEMA 4X; 22 Amp; 15°-140°F/-9°-60°C, ambient t-stat	1	4	0-13627-01332-2	
T9EC	NEMA 4, 7, 9; 22 Amp; 25°-325°F/-4°-163°C, 10 ft capillary	1	5	0-13627-01333-9	
T9EA	NEMA 4, 7, 9; 22 Amp; 15°-140°F/-9°-60°C, ambient t-stat	1	5	0-13627-01334-6	

The following controls are available exclusively for Canada. All items are CSA certified.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
SMC51	Indoor thermostat w/10 ft capillary	1	2	0-13627-00129-9	
SMC52	Indoor thermostat w/20 ft capillary	1	2	0-13627-00214-2	
SMC51WP	Weather-proof thermostat	1	2	0-13627-00097-1	
PPG100	Pre-punched strapping 100 ft	1	5	0-13627-00215-9	

Accessories

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC
NST2	Fiberglass application tape, 3/4" x 36 yds	1	1.5	0-13627-09922-2
ALT1	Aluminum heat transfer tape, 2" x 60 yds	1	2	0-13627-06830-8
CS	Heated Pipe Caution Labels, 5 per bag	1	0.25	0-13627-09924-1