



ET23.5



ET18



E25

**LUMALUX® STANDBY Lamps****DUAL ARC TUBE, INSTANT RESTRIKE<sup>2</sup>, LONG LIFE**

See product information bulletin (HID036) for product details

Watts	Bulb	Base	Product Number	Ordering Abbreviation	ANSI Code/ Fixture Req.	Pkg Qty	Lamp Finish	Operating Position	Avg Rated Life <sup>2</sup> (hrs)	Approx Lumens Initial (Mean)	CRI	CCT (K)	Lamp Efficacy (LPW)
70	ET23.5	E39Mogul	67540	LU70/SBY	S62/0	20	Clear	Universal	40000	6050 (4950)	22	1900	86
100	ET23.5	E39Mogul	67542	LU100/SBY	S54/0	20	Clear	Universal	40000	9500 (7600)	22	2100	95
150	ET23.5	E39Mogul	67544	LU150/55/SBY <sup>1</sup>	S55/0	20	Clear	Universal	40000	15700 (12100)	22	2100	105
200	ET18	E39Mogul	67586	LU200/100/SBY <sup>1</sup>	S66/0	20	Clear	Universal	40000	21500 (18000)	22	2100	108
250	ET18	E39Mogul	67582	LU250/SBY	S50/0	20	Clear	Universal	40000	27500 (23200)	22	2100	110
400	ET18	E39Mogul	67584	LU400/SBY	S51/0	20	Clear	Universal	40000	47500 (40000)	22	2100	119
1000	E25	E39Mogul	67543	LU1000/SBY <sup>3</sup>	S52/0	6	Clear	Universal	30000	127000 (115000)	22	2100	127

<sup>1</sup> LU150/100 (100V) and LU150/55 (55V) lamps are not interchangeable.<sup>2</sup> Standby (instant restrike) feature not guaranteed beyond 24,000 operating hours.<sup>3</sup> Use with 5000V pulse rated sockets only.**PLANTASTAR® Lamps****PLANT GROWTH / HORTICULTURE**

See product information bulletin (HID044) for product details

Watts	Bulb	Base	Product Number	Ordering Abbreviation	ANSI Code/ Fixture Req.	Pkg Qty	Lamp Finish	Operating Position	Avg Rated Life (hrs)	Approx Lumens Initial (Mean)	CRI	CCT (K)	Lamp Efficacy (LPW)
1000	E25	E39Mogul	67314	LU1000/PLANTASTAR <sup>3</sup>	S52/0	6	Clear	Universal	24000	130000 (124000)	22	2100	130