

PRODUCT DATA SHEET

Thread Lubricant, 8 Wt Oz

No. SL35925 | Item# 1007955 | Case# 1007944

Product Description A general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion. Safe for

use on ferrous and non-ferrous metals.

Applications For use on aluminum conduit, bolts, bushings, fittings,

flanges, nuts, pipes, plugs and screws.

Unit Package Description 8 Ounce Bottle

Brand Sta-Lube

Generic Description 1 Thread Lubricant

Net Fill 8 Wt Oz

UPC Code 072213359251

Unit Dimensions 4.25H x 2.5W x 2.5D in

Units Per Case 6

Case Dimensions 4.9H x 4.3W x 7.25D in

Cases Per Pallet 315
Case Weight 4 lbs

I 2 of 5 Code 30072213359252

Appearance Amber Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 334°F
Flash point (C) 168°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.90

Plastic Safe Not Determined

Film Type Grease

Evaporation Rate Very Slow

NLGI Grade 2

Working Temp (F) -20 to 250°F

Working Temp (C) -17.8 to 148.9°C

Propellant None

Last revised: 11/28/2017

Page 1 of 2



 Perfect For Use On Aluminum Conduit and Fittings

Prevents Seizing and Galling

Compare to Crouse-Hinds® STL8

Part No. \$135925 • NET WT. 8 OZ. (227 g)

of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified



PRODUCT DATA SHEET



VOC % (Federal) <0.1

VOC g/L (Federal) <0.9

VOC Lbs./Gal. (Federal) < 0.01

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.



Last revised: 11/28/2017

Page 2 of 2



of CRC Industries, Inc.