

# Surge Protective Devices PanelGuard®

## IG3240RC3



- Type 1 or 2 SPD applications
- 120, 240 VAC Single (Split) phase
- 6 Modes of Surge Protection (L1-N, L2-N, L1-G, L2-G, N-G, L1-L2)
- Green LED indicator provides status of protection
- NEMA 3R Outdoor Raintight Enclosure for Indoor/Outdoor applications
- Metal housing (6.28 in. H x 4.4 in. W x 3.25 in. D)
- 10 year product warranty
- CSA Listed to ANSI/UL 1449 3<sup>rd</sup> Edition
- \$25,000 Connected Equipment Coverage Warranty for 5 years on Appliances and Electronics.



## IG3240FMP3

- Includes faceplate, screws and mounting bracket for IG3240RC3
- 4 x 30 in. 12-gauge color coded leads for the IG1240RC3 or IG3240RC3
- 4 x 24 in. 12-gauge color coded leads for the IG1300-2T-1C3 or IG1300-4T-2C3

## IG Series Chart

Model	Service Voltage	Phase	Leads#/Length (in.)	Gauge	Wire Configuration	I <sub>N</sub> Nominal Discharge Current	SCCR Short Circuit Current Rating	MCOV Maximum Continuous Operation Voltage	VPR Voltage Protection Rating L-N L-L L-G N-G
<b>Type 2</b>									
IG1300-2T-1C3	120, 240 VAC	2	4/24	12	L1, L2, N, GND	20 kA	50 kA	150 L-N, N-G 300 L-L, L-G	700 1200 1200 700
IG1300-4T-2C3	120, 240 VAC	2	4/24	12	L1, L2, N, GND	20 kA	50 kA	150 L-N, N-G 300 L-L, L-G	700 1200 1200 700
<b>Type 1 or 2</b>									
IG1240RC3	120, 240 VAC	2	4/30	12	L1, L2, N, GND	20 kA	50 kA	150 L-N, N-G 300 L-L, L-G	700 1200 1200 700
IG3240RC3	120, 240 VAC	2	4/30	12	L1, L2, N, GND	20 kA	50 kA	150 L-N, N-G 300 L-L, L-G	700 1200 1200 700