

## GLASS FIBER FILLED NYLON ROPE BLOCKS

### Features & Applications

- Shells and sheaves are made of high dielectric, fiber-filled natural nylon
- Shaft is silicon bronze and sheave bearings are oil-impregnated bronze
- Blocks available with Polypropylene or Poly-Dacron rope for minimum stretch and long life
- For working-load considerations, blocks are rated as follows:
  - Double Sheave Blocks, max. 3,500 lb.
  - Triple Sheave Blocks, max. 3,500 lb.
- Dielectric Strength: Dielectric rating in dry weather is 30,000 Volts between bearing and mounting bolt nut
- Maximum rope size is 1/2"

Catalog No.	Description	Weight
C4000919	Double Block with Becket	3 1/4 lb.
C4000918	Triple Block without Becket	3 1/2 lb.

Catalog No.	Description	Weight
C4000914	Two Double Blocks with 120' of 1/2" 3-Str. Polypropylene Rope	12 1/2 lb.
C4000924	Two Double Blocks with 120' of 1/2" 3-Str. Polydacron Rope	16 1/4 lb.
C4000915	Double and Triple Blocks with 150' of 1/2", 3-Str. Polypropylene Rope	16 lb.
C4000925	Double and Triple Blocks with 150' of 1/2", 3-Str. Polydacron Rope	20 1/2 lb.
T4001257	Two Double Blocks with 120' of 1/2", Composite Fiber Braided Rope	14 1/2 lb.
T4001258	Double and Triple Blocks with 150' of 1/2", Composite Fiber Braided Rope	16 1/2 lb.



### HAND LINE BLOCK, SAFETY ORANGE

- 1,000 lb. working load
- Safety orange color
- Fiberglass reinforced nylon body & sheave
- Side-opening body design for easy rigging

Catalog No. PSC4033478  
 Weight: 1 1/4 lb. (0.57 kg.)  
 Rated working load: 1,000 lb. (454 kg.)

### Features & Applications

- 3"-diameter sheave accepts up to 5/8"-diameter rope
- Plated-steel swivel eye allows 360\* orientation
- Plated-forged-steel hook has 3/4 throat opening, plus spring-loaded safety latch
- Side-opening design includes high-strength detent-ball pin that is easy to remove and is secured to body with a lanyard

### Components available as separate items

Catalog No.	Description	Weight
PSC4033479	Lanyard and Pin Kit	1/4 lb. / 0.11 kg.
PSC4033480	Spring Latch Kit	1/8 lb. / 0.05 kg.

## SNATCH BLOCKS

### Features & Applications

- Lightweight, cast-aluminum housing and sheave with hinged, cotter-lock yoke and either forged-steel or steel meat hook makes for quick, easy rigging in various applications
- Hand line and block and tackle efficiency is increased with forged-steel, swivel-eye suspension ring, plus three-inch sheave operating on bronze oilite bearings
- Maximum rope size is 5/8"
- Maximum load capacity is 1,250 lbs. on 2230 Series only



C4176067 or 22301      22302

Catalog No.	Description with Retainer Latch	Weight
22301	1250 lb. Block with forged steel hook	2 lb./ .9 kg.
22302	1250 lb. Block with steel meat hook	2 lb./ .9 kg.
C4176067	2500 lb. Block with forged steel hook	6 lb./ 2.7 kg.
PS400006	Ball Lok Pin Chain for 22301 or 22302	1/4 lb./ 0.11 kg.



M1849

## HAND LINE HOOK

### Features & Applications

- Hook can be attached any place along the hand line by two large holes
- The long point accommodates most items to be raised and lowered at the pole
- Maximum load of hook is 500 lbs. with load seated at bottom of hook