

Staples

Used to secure ground wire and ground wire molding to wood poles.



† RUS listed
 * ANSI Standard
 ‡ RUS Listing Pending

| Staple Type | Dimensions (Inches) Length x Inside Width x Wire Dia. | FINISH | | | | | | | |
|--------------------------------------|--|-----------------------------|----------------------------|-----------------------------------|----------------------------|-----------------------------------|----------------------------|---------------------------------|----------------------------|
| | | ELECTRO ZINC Catalog No. | | GALVANIZED Catalog No. | | COPPER COATED Catalog No. | | BRIGHTWIRE Catalog No. | |
| | | Qty per carton /inner pkg. | Approx. Wt. (lbs.) per 100 | Qty per carton /inner pkg. | Approx. Wt. (lbs.) per 100 | Qty per carton /inner pkg. | Approx. Wt. (lbs.) per 100 | Qty per carton /inner pkg. | Approx. Wt. (lbs.) per 100 |
| Barbed | 1-1/2 x 3/8 x .131 | | | C2050460 ‡ 1750/350 1.4 | | | | | |
| | 1-1/2 x 3/8 x .140 | | | | | C2050464 ‡ 1500/300 1.7 | | | |
| | 2 x 3/8 x .131 | | | C2050461 1300/260 1.9 | | | | | |
| | 2 x 5/8 x .165 | | | C2050463 800/160 3.2 | | | | | |
| | 3 x 1-1/16 x .218 | | | C2050462 ‡ 300/60 8.3 | | | | | |
| Rolled (Diamond) Point | 1 x 1/4 x .114 | | | | | C2050223 5000/500 0.5 | | | |
| | 1 x 5/16 x .120 | 7511 1000/100 | 0.5 | C2050213 1000/100 | 0.5 | | | | |
| | 1-1/4 x 1/4 x .114 | | | | | C2050224 5000/500 0.6 | | | |
| | 1-1/2 x 5/16 x .144 | | | | | C2050225 2500/500 1.2 | | | |
| | 1-1/2 x 3/8 x .148 | C2050207 1000/100 | 1.4 | C2050214* 1000/100 | 1.4 | | | C2050235 1000/100 1.4 | |
| | 1-3/4 x 3/8 x .144 | | | | | 9153 2500/500 1.4 | | | |
| | 1-3/4 x 3/8 x .148 | C2050208 1000/100 | 1.5 | C2050215* 1000/100 | 1.5 | | | | |
| | 2 x 1/2 x .162 | 7512 1000/100 | 2.2 | C2050216*† 1000/100 | 2.2 | 9154 1000/100 | 2.2 | C2050237 1000/100 | 2.2 |
| | 2 x 5/8 x .162 | C2050209 1000/100 | 2.3 | C2050217 1000/100 | 2.3 | C2050226 1000/100 2.3 | | | |
| | 2 x 5/8 x 3/16 | C2050210 1000/100 | 3.2 | C2050218 1000/100 | 3.2 | | | | |
| | 2 x 1-1/16 x 3/16 | 7513 1000/100 | 3.1 | C2050219* 1000/100 | 3.1 | C2050229 1000/100 3.1 | | | |
| | 2-1/4 x 25/32 x 3/16 | | | | | C2050227 1000/100 3.4 | | | |
| | 2-1/2 x 1-1/16 x 3/16 | | | | | C2050230 1000/100 4.0 | | | |
| | 3 x 1 x 1/4 | | | | | C2050232 500/100 8.0 | | | |
| | 3 x 1-1/16 x 1/4 | 7522 500/100 | 8.0 | C2050220 500/100 | 8.0 | 9161 † 500/100 8.0 | | | |
| | 3 x 1-1/2 x 1/4 | C2050211 500/100 | 8.0 | C2050221 500/100 | 8.0 | C2050233 500/100 | 8.0 | C2050242 500/100 | 8.0 |
| 3-1/2 x 1-3/4 x 1/4 | C2050212 250/100 | 9.5 | C2050222 250/50 | 9.5 | | | | | |
| Cut (Slash) Point | 1-1/4 x 3/16 x .114 | | | | | C2050245 6700/NA 0.7 | | | |
| | 1-3/8 x 1/2 x .162 | | | | | C2050244 3100/NA 2.0 | | | |
| | 1-1/2 x 1/4 x .148 | 751134 3600/NA | 2.0 | C2050247 † 3600/NA | 2.0 | | | | |
| | 1-1/2 x 3/8 x .162 | | | | | 9167 † 2900/NA 2.0 | | | |
| | 2 x 1/2 x .162 | | | | | 9169 2200/NA 2.0 | | | |