

TPS3 09

Type 1 Surge Protective Device (SPD)

Mounts External to Electrical Distribution Equipment or Internal to P1, P2 Lighting Panelboards, P3 Power Panelboards and Busway Systems

Features:

- UL 1449 3rd Edition – 2009, cUL
- Type 1 SPD (Type 2 cUL)
- Mounts external to electrical distribution equipment
 - Weatherproof hub included
- Mounts internal to P1 panelboards & busway
 - P1 - Field retrofit or factory install
 - P2 and P3 - Factory install only
Consult factory for field retrofit
- Large block, individually fused, thermally protected, 50kA MOV's
- 20kA I_n (most models)
- 200kA SCCR (most models)
- All UL-required OCP & safety coordination included
- UL96A Lightning Protection Master Label compliant (@20kA I_n)
- SPD Specifications
 - Surge Current Rating Per Phase

Per Phase	L-N	L-G	N-G
100kA	50kA	50kA	50kA
 - 100% monitoring – Every MOV is monitored, incl. N-G
 - Individually fused and thermally protected MOV's
 - Solid state bi-directional operation
 - Repetitive impulse: 5,000 hits
 - Less than 1 nanosecond response time
 - Relative humidity range: 0 -95% non-condensing
 - Operating frequency: 47-63Hz
 - Operating temperature: -25°C (-15°F) to +60°C (140°F)
- Standard Configuration
 - Standard NEMA 4X polycarbonate enclosure (UL 746C (f1), UL 94-5VA)
 - Wire size: Prewired with 3' (91.4cm) of #10 AWG
 - Standard size: 8" x 3" x 3" (203mm x 76mm x 76mm)
 - Standard weight: 3 lbs. (1.4 kg)



UL 1449 3rd Edition SPD

SIEMENS

■ SPD Features

- UL 1449 3rd Edition effective September 2009
- Designed, manufactured and tested consistent with:
 - ANSI/IEEE C62.41.1-2002, c62.41.2-2002, C62.45-2002,
 - 1992/2000 NEMA LS-1
 - NEC Article 285
 - IEC 61643, CE

■ SPD Features

- Large block, individually fused, thermally protected, 50kA MOV's
 - 10 year warranty
- SPD Monitoring
- LED indicators
- Available Options
- Dry contacts & audible alarm

■ Key Bid Specifications

- UL 1449 3rd Edition – 2009, cUL
- Type 1 SPD (Type 2 cUL)
- Protection modes on L-N, L-G, L-L, N-G
- I_{in} Rating – 20kA
- Short Circuit Current Rating – 200kA
- Surge Current Rating
Per Phase = L-N + L-G
100kA 50kA 50kA

Ordering Information

Catalog #

TPS3 09

Voltage Code

- A = 120/240V, 1Ø, 3W (Fig 1)
- B = 120/240V, 3Ø, 4W (Fig 3)
- C = 120/208V, 3Ø, 4W (Fig 2)
- D = 240V, 3Ø, 3W (Fig 4)
- E = 277/480V, 3Ø, 4W (Fig 2)
- F = 480V, 3Ø, 3W (Fig 4)
- G = 600V, 3Ø, 3W, (Fig 2)
- K = 380/220V, 3Ø, 4W (Fig 2)
- L = 600/347V, 3Ø, 4W (Fig 2)
- S = 400/230V, 3Ø, 4W (Fig 2)

Surge Current (kA)

- 10 = 100kA per phase

Options

- E = Extended indicator light

- I = Internal mounting in P1, P2 panels*

- D = Dry contact & audible alarm

*Requires TPS9IKITP1 or TPS9IKITP2 mounting bracket accessory, see below

- Example: TPS3C0910D00 = SPD for a 208/120V panelboard with a surge current capacity of 100kA per phase with standard NEMA 4X enclosure, dry contacts and audible alarm option.
- Available for field retrofit in P1 panels
- When an option is not selected, include a zero (0) in the field

Available accessories: Must be ordered separately

- RMSIE = Remote monitor
- FMKITC = Flush mount plate
- TPS9IKITP1 = Mounting bracket for installation in P1 panels
- TPS9IKITP2 = Mounting bracket for installation in P2 panels

UL 1449 3rd Edition - 2009 Test Data Summary

Voltage Protection Rating (VPR - 6kV, 3kA)

Voltage Code	Service Voltage	L-N	L-G	N-G	L-L	Type*	I_{in}	SCCR	MCOV
A	120/240V, 1Ø, 3W (Fig 1)	600	700	500	1000	Type 1	20kA	100kA	150
B	120/240V, 3Ø, 4W (Fig 3)	600 / 1200	700 / 1200	500	1000 / 1000	Type 1	20kA	200kA	150 / 320
C	120/208V, 3Ø, 4W (Fig 2)	600	700	500	1000	Type 1	20kA	200kA	150
D	240V, 3Ø, 3W (Fig 4)		1200		1200	Type 1	20kA	200kA	320
E	277/480V, 3Ø, 4W (Fig 2)	1200	1200	1000	1800	Type 1	20kA	200kA	320
F	480V, 3Ø, 3W (Fig 4)		1800		1800	Type 1	10kA	200kA	552
G	600V, 3Ø, 3W (Fig 2)		2500		2500	Type 1	10kA	200kA	690
K	380/220V, 3Ø, 4W (Fig 2)	1200	1200	1000	1800	Type 1	20kA	200kA	320
L	600/347V, 3Ø, 4W (Fig 2)	1500	1500	1500	2500	Type 1	10kA	200kA	420
S	400/230V, 3Ø, 4W (Fig 2)	1200	1200	1000	1800	Type 1	20kA	200kA	320

* Type 2 cUL




Figure 1




Figure 2




Figure 3




Figure 4

Split
2 Hots, 1 Neu, 1 Grnd

Wye
3 Hots, 1 Neu, 1 Grnd

Hi-Leg Delta (B High)
3 Hots, (B High),
1 Neu, 1 Grnd

Delta & HRG Wye
3 Hots, 1 Grnd

Siemens Industry, Inc.
Building Technologies Division
5400 Triangle Parkway
Norcross, GA 30092

1-800-964-4114
info.us@siemens.com

©2009 Siemens Industry, Inc.
All Rights Reserved. Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications are subject to change without notice.

RPFL-IADT1-0809 (New)

www.usa.siemens.com/spd