

FIBERGLASS

375 lbs. TYPE IAA
load capacity*

STEP-TO-STRAIGHT LADDER FC1200 SERIES



- Hinging Mechanism
- Standard Pole Grip
- Utility-Style safety shoes
- Double-rivet step construction
- Rung Lock



MODEL	SIZE	MAX. EXT. LENGTH	FLARED SECTION MIN. O.D.	FLARED SECTION MAX. O.D.	PARALLEL SECTION O.D.	APPROX. WT. (LBS)	APPROX. CUBES
FC1206	6'	9'	17 7/8"	23 5/8"	14 5/8"	33	6.8'
FC1207	7'	11'	17 7/8"	24 5/8"	14 5/8"	36	8.0'
FC1208	8'	13'	17 7/8"	25 5/8"	14 5/8"	41	9.3'



FIBERGLASS

375 lbs. TYPE IAA
load capacity*

PLATFORM LADDER FP1400HD SERIES



- Da Boot™ Patent #7,000,731 B2
- Top rail Guard
- Slip resistant platform
- 375 lb. Rated rail
- Riveted step construction with Gussets



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FP1404HD	4'	3"	25 1/8"	44"	24	5.4'
FP1405HD	5'	3"	26 5/8"	50"	28	6.8'
FP1406HD	6'	3"	28 1/8"	56"	32	8.2'
FP1408HD	8'	3"	31 1/8"	68"	42	10.9'
FP1410HD*	10'	3"	34 1/8"	80"	56	13.6'
FP1412HD*	12'	3"	37 1/8"	92"	68	16.3'

*SPECIAL DUTY: MANUFACTURED TESTED TO 375 LBS.

FIBERGLASS

300 lbs. TYPE IA
load capacity*

PLATFORM LADDER FP1500 SERIES



- Da Boot™ Patent #7,000,731 B2
- Slip resistant platform
- Top rail Guard
- Double-rivet step construction
- Full channel fiberglass rail
- Heavy Gusset Bracing



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FP1504	4'	3"	25 1/8"	44"	24	5.4'
FP1505	5'	3"	26 5/8"	50"	26	6.8'
FP1506	6'	3"	28 1/8"	56"	29	8.2'
FP1508	8'	3"	31 1/8"	68"	43	10.9'
FP1510	10'	3"	34 1/8"	80"	55	13.6'
FP1512	12'	3"	37 1/8"	92"	66	16.3'