



TRIPLE S® INTUMESCENT SEALANT



Premium grade, water-based firestop caulk featuring STI's patented two-stage intumescent technology. The perfect choice for the broadest array of combustible and non-combustible electrical penetrants requiring a permanent, durable seal.

FEATURES & BENEFITS:

- Suitable for all forms of construction including industrial and complex commercial and institutional facilities.
- Patented two-stage intumescent technology.
- Shear thins when caulked to easily seal between cables and conduits.
- Broadest range of tested and compliant firestop systems.
- UL Tested and Classified for all common constructions up to and including 4 hours. FM Approved.
- Acoustically tested and proven to reduce sound transmission.
- UL leakage tested (L Ratings).
- Water-based - easy cleanup, installation and disposal.
- Safe to use, low VOCs, no solvents, non-halogenated.
- Red color for easy identification and inspection.



APPLICATIONS

- Single or multiple metallic conduits & tubing.
- Single or multiple non-metallic conduits & tubing.
- Electrical cables including all common types & sizes.*
- Cable trays & bus ducts.

*Recommended for cables that can be permanently sealed.



ORDERING INFORMATION

UPC #	Part #	Description	Qty.	Case Qty.	Weight Each - lbs.
01100	SSS100	Intumescent Sealant 10.1 oz. Tube (18.2 Cu. In., 300 ml)	1	12	0.90
01102	SSS102	Intumescent Sealant 2 gal. Pail (462 Cu. In., 7.6 L)	1	n/a	20.00
01105	SSS105	Intumescent Sealant 5 gal. Pail (1155 Cu. In., 19.0 L)	1	n/a	50.00
01103	SSS120	Intumescent Sealant 20 oz. Sausage (36 Cu. In., 592 ml)	1	12	1.55
01129	SSS129	Intumescent Sealant 29 oz. Tube (52 Cu. In., 858 ml)	1	10	2.49



LCI INTUMESCENT SEALANT



Standard grade, water-based firestop caulk engineered to address most common combustible and non-combustible electrical applications typically found in light commercial construction.

FEATURES & BENEFITS:

- Suitable for common forms of construction including light commercial and grouped residential.
- Wide range of tested and compliant firestop systems.
- UL Tested and Classified for all common constructions up to and including 3 hrs.
- Acoustically tested and proven to reduce sound transmission.
- UL leakage tested (L Ratings).
- Water-based - easy cleanup, installation and disposal.
- Safe to use, low VOCs, no solvents, non-halogenated.
- Pale red color for easy identification and inspection.



APPLICATIONS

- Single or multiple metallic conduits & tubing.
- Single or multiple non-metallic conduits & tubing.
- Electrical cables including all common types & sizes.*

*Recommended for cables that can be permanently sealed.



ORDERING INFORMATION

UPC #	Part #	Description	Qty.	Case Qty.	Weight Each - lbs.
01170	LCI300	Intumescent Sealant 10.1 oz. Tube (18.2 Cu. In., 300 ml)	1	12	0.94
01175	LCI305	Intumescent Sealant 5 gal Pail (1,155 Cu. In., 19.0 L)	1	n/a	50.00
01172	LCI320	Intumescent Sealant 20 oz. Sausage (36 Cu. In., 592 ml)	1	12	1.59
01179	LCI329	Intumescent Sealant 29 oz. Tube (52 Cu. In., 858 ml)	1	10	2.27

