

READY™ SLEEVE



A complete code compliant firestop sleeve assembly for new cable installations. Includes all mounting hardware and internal and external firestop sealing materials. Available in 1", 2", and 4" sizes with standard or large escutcheon plates.

FEATURES & BENEFITS:

- Complete! Includes sleeve, all mounting hardware, firestopping materials.
- Saves money by reducing expensive shop and field labor.
- Standard and large escutcheons available.
- Meets code requirements for internal/external firestop sealing.
- Meets code requirements for wall attachment.
- Built-in bushings protect cables.*
- Includes SpecSeal® Series SSP Intumescent Firestop Putty sufficient for 1" (25 mm) depth at both ends.
- UL Classified (up to 4 hr.)

* Standard for 2" (60 mm OD) and 4" (114 mm OD) sizes. Separate bushing provided for 1" (25 mm).



APPLICATIONS

- Protect, support and seal cables routed through rated and non-rated walls & floors.
- All common constructions up to 10" (250 mm) thick.
- Available trade sizes 1" (33 mm OD), 2" (60 mm OD), 4" (114 mm OD).
- Standard small escutcheons for accurate gypsum board openings.
- Large escutcheons for concrete or masonry openings.



ORDERING INFORMATION					
UPC #	Part #	Description	Qty.	Case Qty.	Weight Each - lbs.
20100	FS100	1 in. (25 mm) Firestop Sleeve	1	6	1.00
20200	FS200	2 in. (51 mm) Firestop Sleeve	1	6	2.00
20400	FS400	4 in. (102 mm) Firestop Sleeve	1	6	4.00
20201	FS201	2 in. (51 mm) Firestop Sleeve w/ large escutcheon plates	1	n/a	2.90
20401	FS401	4 in. (102 mm) Firestop Sleeve w/ large escutcheon plates	1	n/a	4.80

READY™ SPLIT SLEEVE



Ready™ Sleeve convenience for existing cable installations. Split sleeve and two-piece wall plates allow sleeve to be assembled around cables and locked into the wall or floor. Available in 1", 2", and 4" sizes.

FEATURES & BENEFITS:

- Complete! Includes split sleeve, all mounting hardware, firestopping materials.
- Over-sized plates for larger or irregular openings.
- Built-in bushings protect cables.
- Meets code requirements for internal/external firestop sealing.
- Optional wall attachment points provided for sleeve stabilization.
- Includes SpecSeal® Firestop Putty as well as split external firestop gasket.
- UL Classified (up to 4 hr.).



APPLICATIONS

- New or existing cable installations through walls or floors.
- All common constructions up to 10" (250 mm) thick.
- Available trade sizes 1" (33 mm OD), 2" (60 mm OD), 4" (114 mm OD).
- Oversized or irregular openings.



ORDERING INFORMATION					
UPC #	Part #	Description	Qty.	Case Qty.	Weight Each - lbs.
21000	FSR100	1 in. (25 mm) Split Firestop Sleeve	1	4	1.25
22000	FSR200	2 in. (51 mm) Split Firestop Sleeve	1	4	2.50
24000	FSR400	4 in. (102 mm) Split Firestop Sleeve	1	4	6.25

