



- Driller Toggle
- Reusable
- Includes Screws & Power Bit
- Metal/Engineered Plastic

CAT NO	UPC	CONTENTS	STD	MSTR	WT/STD	UNIT
WDT83	81022	35-1/8" Driller Toggle (1/8" x 3" Truss Hd. Mach. Screws)	1	6	1.10#	Ea
WDT363	81023	25-3/16" Driller Toggle (3/16" x 3" Truss Hd. Mach. Screws)	1	6	1.65#	Ea
WDT43	81024	20-1/4" Driller Toggle (1/4" x 3" Truss Hd. Mach. Screws)	1	6	1.65#	Ea

DRYWALL THICKNESS	TEST RESULTS	
	TENSION (LBS)	SHEAR (LBS)
3/8"	87	231
1/2"	106	253
5/8"	160	285

NOTE: The values listed above are ultimate load capacities which should be reduced by a minimum safety factor of 4 or greater to determine the allowable working load.



FEATURES

- No Pre-Drilling
- Quick & Easy
- Ideal for Ceiling Applications
- Combo Truss Head Screws
- Versatile for 3/8", 1/2" and 5/8" Drywall!
- Includes Phillips Power Bit

**Nylon Button Head and Toggle Anchor Kits
PC 4610**

- 100 Nylon Button Head Anchors With Pin
- 25 Nylon Toggle Anchors
- 1 Carbide Masonry Drill
- 25 Sheet Metal Screws
- Display or Tuff Pack
- 1 Carbide Masonry Drill
- Display or Tuff Pack



CAT NO	UPC	D-DISPLAY PACK T-TUFF PACK	SIZE	ANCHOR TYPE	DRILL	STD	MSTR	WT/STD	UNIT
Nylon Button Head Anchors with Pins									
711	18535	D	3/16 x 1"	1711	3/16"	1	10	0.67#	Ea
711TP	18537	T	3/16 x 1"	1711	3/16"	1	10	0.67#	Ea
714	18540	D	1/4 x 1"	1714	1/4"	1	10	0.72#	Ea
714TP	18545	T	1/4 x 1"	1714	1/4"	1	10	0.72#	Ea

Nylon Toggle Anchors with Screws

NTK14L	66797	D	8 x 1-1/2"	NT14L	1/4"	1	10	0.39#	Ea
NTK14LTP	66800	T	8 x 1-1/2"	NT14L	1/4"	1	10	0.39#	Ea
NTK38L	66799	D	10 x 1-1/2"	NT38L	3/8"	1	10	0.49#	Ea
NTK38LTP	66802	T	10 x 1-1/2"	NT38L	3/8"	1	10	0.49#	Ea

**Strap Toggle Kits
PC 4735**



- Strap Toggle
- Nylon
- Includes Screws
- Reusable

The strap toggle is a heavy duty hollow wall anchor for use in base materials such as plaster, wallboard, or hollow tile. The strap toggle is a preassembled anchor consisting of a carbon steel wing and a locking cap/ratchet leg assembly molded from engineered plastic. It is available in both 3/16" and 1/4" size. When compared to traditional toggles, this unique anchor can be installed in a smaller hole and does not require a fixture or screw to set it. The anchor can easily be adjusted to accommodate a wall thickness of up to 2-1/2". The toggle remains captive.

CAT NO	UPC	DESCRIPTION	STD	MSTR	WT/STD	UNIT
STK36	10524	25 3/16 x 4" Strap Toggles and 25 3/16 x 4" Mushroom Head Screws	1	10	1.67#	Ea
STK25	10526	25 1/4 x 4" Strap Toggles and 25 1/4 x 4" Mushroom Head Screws	1	10	1.89#	Ea