


**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YGL29C29  
 7818102200233  
 2-250 TO 2-250 GRD GRID/  
 Active



**Web Use**  
 BURNDY Product Line



Length (in)  
 B Length (in)  
 BB - Length (in)

**Dimensional**  
 2.50  
 0.75  
 0.75

Product Description

**General**  
 Copper Compression Cross Grid  
 Connector, 2 AWG (Str)-250 kcmil  
 or 1/2"-5/8" Rod or #3-4 Rebar, 2  
 AWG (Str)-250 kcmil

Prefilled (Oxide Inhibitor)

Y

Type of Oxide Inhibitor

**Other**  
 Penetrox E

Rated for Direct Burial

**Approvals / Certifications**

Y

UL Listed

Y

CSA Certified

Y

ROHS Compatible

Compliant

UL Recognized

N

CULUS

N

Industry Standards

UL467,IEEE 837

Rod Size (Side A) - Range

**Conductor(s)**  
 1/2 in-5/8 in

Rod Size (Side B) - Range

N/A

Rebar Size (Side B) - Range

N/A

Copper Solid Size (Side A) - Range

N/A

Copper Str Size(Side B) - Range

2 AWG-250 kcmil

Copper Str Size (Side A) - Range

2 AWG-250 kcmil

CopperSolid Size (Side B) - Range

N/A

Rebar Size (Side A) - Range

3 -4

Type of Plating

**Physical**  
 Unplated

Plated (Yes or No)

N

Index Number

997

Product Material

Copper

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175