




Pushbutton Units and Indicator Lights

Class 51, Hazardous Location NEMA Type 7 & 9 Devices

Accessories and spare parts

Selection and ordering data

Version	Suitable for	Conduit size (in.)	Color	Order No.	List Price \$ 1 unit	Pack Unit	
	Cast aluminum, UL recognized and CSA certified. Used to reduce existing tapered NPT conduit opening when required.	3/4 - 1/2		51AARBA		1	
		1 - 1/2		51AARCA			
		1 1/2 - 3/4		51AARDB			
		1 1/2 - 1		51AARDC			
		2 1/2 - 3/4		51AARFB			
		2 1/2 - 1		51AARFC			
		2 1/2 - 1 1/2		51AARFD			
		2 1/2 - 2		51AARFE			
		3 - 1		51AARGC			
		3 - 1 1/2		51AARGD			
		3 - 2		51AARGE			
3 - 2 1/2		51AARGF					
Lamps with screw connection, miniature bayonet incandescent lamps							
	Flashing, type 267 lamp (replaces 755 lamp)	51, 52	6V	52AABNF		1	
	6V Full voltage, transformer type 755 lamp	51, 52	6V	52AABN		1	
	12V full voltage, type 756	51, 52	12V	52AACN		1	
	24V full voltage, 120/240V resistor push-to-test type 757	51, 52	24V	52AADN		1	
	Neon (uses resistors) type B2A (NE-51H)	51, 52	120V	52AAPN		1	
	120V, full voltage type 3S6/5	51, 52	120V	52AAENC		1	
	LEDs, Single element	51, 52	6V	Red	52AEB2		1
		51, 52	6V	Green	52AEB3		
		51, 52	6V	Yellow	52AEB4		
		51, 52	6V	White	52AEBB		
		51, 52	6V	Blue	52AEB5		
51, 52		24V	Red	52AED2			
51, 52		24V	Green	52AED3			
51, 52		24V	Yellow	52AED4			
51, 52		24V	White	52AEDB			
51, 52		24V	Blue	52AED5			
51, 52		120V	Red	52AEE2			
51, 52		120V	Green	52AEE3			
51, 52		120V	Yellow	52AEE4			
51, 52		120V	White	52AEEB			
51, 52		120V	Blue	52AEE5			
Touchsafe contact blocks with gold flashing							
	1 NO			52BAK		1	
	1 NC			52BAJ			
	1 NO - 1 NC			52BJK			
	1 NO early make	closes before 52BAK		52BAH			
	1 NC late break	opens after 52BAJ		52BAE			
	1 NO - 1 NC	Reed switch		52BAR ¹⁾			
		UL listed for class 1 division 2					
		.25A Max, 150V AC, 10 Watt max					
		.5A Max, 150V DC, 10 Watt max					
	1 NC extra late break			52BAU			

1) Hermetically sealed.