

## Mobile VersiBoom™ II

**NEW**  
PRODUCT



Mobile VersiBoom™ II shown with Ultra Tugger® 10, sold separately.

### Quick Set-Up

- One person set-up in less than 2 minutes.

### Versatile

- Can be extended up to 20'.
- Use with one 3' boom for tighter spaces.
- Use with 2"-5" slip-on adapters and 2"-4" threaded adapters.

### Easy to store and transport

- Can be folded up in less than 2 minutes and can be stored on the back of a pick-up truck.
- Fully contained unit.

#### SPECIFICATIONS

<b>Weight</b>	322 lbs. (146.06 kg)
<b>Length</b>	47" (1193.8mm)
<b>Width</b>	42" (1066.8 mm)
<b>Height</b>	48" (1219.19 mm)

CAT. NO.	UPC NO.	DESCRIPTION
MVB	00553	Mobile VersiBoom™ II
00560	00560	4' boom
00561	00561	3' Boom
00562	00562	Elbow/Nose Assembly
00564	00564	2-1/2" Adapter
00565	00565	3" Adapter
00567	00567	4" Adapter
00588	00588	Short Hanger
00589	00589	Long Hanger

## Mobile VersiBoom™ II Components/Accessories



CAT. NO.	UPC NO.	DESCRIPTION	SHIPS WITH MVB II
<b>A</b> 00471	00471	Coupling Hanger Kit	
<b>A</b> 00563	00563	Adapter Weldment, 2" (UT8)	
<b>R</b> 00564	00564	Adapter Weldment, 2-1/2"	✓
<b>R</b> 00565	00565	Adapter Weldment, 3" (UT8)	✓
<b>A</b> 00566	00566	Adapter Weldment, 3-1/2"	
<b>R</b> 00567	00567	Adapter Weldment, 4" (UT8)	✓
<b>A</b> 00583	00583	Adapter Assembly, 2" Screw-On	
<b>A</b> 00584	00584	Adapter Assembly, 2-1/2" Screw-On	
<b>A</b> 00585	00585	Adapter Assembly, 3" Screw-On	
<b>A</b> 00586	00586	Adapter Assembly, 3-1/2" Screw-On	
<b>A</b> 00587	00587	Adapter Assembly, 4" Screw-On	
<b>R</b> 00588	00588	Hanger Weldment, Short	✓
<b>R</b> 00589	00589	Hanger Weldment, Long	✓
<b>A</b> 00590	00590	Screw On Coupling Kit	
<b>A</b> 00610	00610	Adapter Weldment, 5" (UT8)	
<b>R</b> 00561	00561	3' Boom	✓
<b>R</b> 00560	00560	4' Boom	✓

Rope is a very critical link in the cable pulling system. See page 99 for proper pulling rope selection.

## G3 Tugger™ 2 Cable Puller



- Clamp easily adjusts for different sizes of conduit.
- Right angle sheave safely keeps operators out of direct line of pulls.
- Portable handle and wheels for increased mobility around jobsites.
- Change tail length, pull direction, and angle of pull with ease.
- Can hook on the back of a truck hitch.
- Customized motor with circuit breaker specifically designed for cable pulling.

### SPECIFICATIONS

<b>Pulling Force</b>	Continuous rating	1,200 lbs.
	Intermittant rating	2,000 lbs.
<b>Drive Motor</b>	120 VAC, 50/60 Hz, 12 Amps	
<b>Weight</b>	123 lbs.	
<b>Pulling Speeds</b>	High Speed capstan	
	No Load:	97 ft/min
	500 lb. Load (227 kg)	59 ft/min
	1,000 lb. Load (455 kg)	36 ft/min
	Low Speed Capstan	
<b>Pulling Rope</b>	No Load:	41 ft/min
	1,000 lb. Load (455 kg)	21 ft/min
	2,000 lb. Load (909 kg)	13 ft/min
	1/2" polyester (10,000 lb. minimum breaking strength) *Greenlee recommends that only low stretch polyester rope be used with the G3. High stretch ropes can release large amounts of energy should they break during use.	
<b>Conduit Size</b>	1" or larger	
<b>Pulling Capabilities</b>	3 x 500 kcmil cable 500' with 2 x 90° bends	
	3 x 500 kcmil cable 250' with 4 x 90° bends	
	8 x 4/0 AWG cable 300' with 3 x 90° bends	



CAT. NO.	UPC NO.	DESCRIPTION
G3	00905	G3 Tugger™

Rope is a very critical link in the cable pulling system. See page 99 for proper pulling rope selection.