

Rubber Low Pressure Hose, Red, Non-Conductive

130694



- Certified nonconductive red rubber.
- Double rayon braid.
- Working pressure 2,250 psi (155 bar) tested to 75 kV/ft. for five minutes.

CAT. NO.	UPC NO.	DESCRIPTION
130694	40635	Two 3/8" x 8' (10 mm x 2.4 m) I.D. Hoses with 3/8" NPTF male fittings
130696	40637	Two 3/8" x 10' (10 mm x 3 m) I.D. Hoses with 3/8" NPTF male fittings
104101K2	40164	Two 3/8" x 8' (10 mm x 2.4 m) I.D. Hoses with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" NPTF male fitting on the other hose
104102K2	40165	Two 3/8" x 10' (10 mm x 3 m) I.D. Hoses with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" NPTF male fitting on the other hose

Note: Hose assemblies above do not come with quick-disconnect couplers, they must be ordered separately.

Polyurethane Low Pressure Hose, Orange, Non-Conductive

108271



- Certified nonconductive orange polyurethane.
- Double rayon braid.
- Working pressure 2,250 psi (155 bar) tested to 75 kV/ft. for five minutes.

CAT. NO.	UPC NO.	DESCRIPTION
108271	40250	Two 3/8" x 8' (10 mm x 2.4 m) I.D. Hoses with 3/8" NPTF male fitting on one hose and 1/2" NPTF male fitting on the other hose
108272	43036	Two 3/8" x 10' (10 mm x 3 m) I.D. Hoses with 3/8" NPTF male fitting on one hose and 1/2" NPTF male fitting on the other hose

Note: Hose assemblies above do not come with quick-disconnect couplers, they must be ordered separately.

Low Pressure Hose, Conductive



- Steel (conductive). NOTE: Steel braid hoses are not intended for use near energized lines or equipment!
- Wire braid reinforced.
- SAE 100R1 AT Hose.
- Working pressure 2,000 psi (138 bar)

CAT. NO.	UPC NO.	DESCRIPTION
111185	40284	Two 1/2" x 25' (13 mm x 7.6 mm) wire braid hoses with 1/2" NPTF male fittings at both ends

Note: Hose assembly above does not come with quick-disconnect couplers, they must be ordered separately.

Whip Hose Set, Conductive



- For use in place of quick-disconnect body assemblies on tool.
- Allows any type coupling to be used.
- Working pressure 2,000 psi (138 bar).

SPECIFICATIONS

Length 8" (203 mm)

CAT. NO.	UPC NO.	DESCRIPTION
101243	40111	Hose Fittings – Two hoses. One 8" (203 mm) hose with 3/8" NPTF Male x 9/16 - 18 SAE O-ring and One 8" (203 mm) hose with 3/8" NPTF Male x 3/4 - 16 SAE O-ring.