

## Branch Switch Selection

| Ampere Rating   | Mounting Height (inches) |
|---|--------------------------|
| <b>240V — Twin Mounted NEC Fuse Clips<sup>②</sup></b>   |                          |
| 30-30   | 2½ <sup>③</sup>          |
| 30-30   | 5                        |
| 30-60   | 5                        |
| 60-60   | 5                        |
| 60-100  | 7½                       |
| 100-100   | 7½                       |
| 200-200   | 10                       |
| <b>240V — Single Mounted NEC Fuse Clips<sup>②</sup></b> |                          |
| 30  | 7½                       |
| 60  | 7½                       |
| 100   | 7½                       |
| 200   | 10                       |
| 200   | 7½                       |

| Ampere Rating   | Mounting Height (inches) |
|---|--------------------------|
| <b>600V — Twin Mounted NEC Fuse Clips<sup>②</sup></b>   |                          |
| 30-30   | 7½                       |
| 30-60   | 7½                       |
| 60-60   | 7½                       |
| 60-100  | 7½                       |
| 100-100   | 7½                       |
| 200-200   | 10                       |
| <b>600V — Single Mounted NEC Fuse Clips<sup>②</sup></b> |                          |
| 100   | 7½                       |
| 200   | 10                       |

## Type S4/P4/SPP (10" deep) and F1/P4/FPP (10" deep)

### Connecting Strap Kits — w/o Circuit Breaker

| For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards |                |                 |                             |                      |          |
|--|----------------|-----------------|-----------------------------|----------------------|----------|
| Max Amp Rating   | Breaker Family | Breaker Type    | Catalog Number <sup>①</sup> | Unit Height (inches) | Mounting |
| 100  | General        | BL, BQD         | SBL                         | 3.75                 | Twin     |
| 125  | General        | NGB, HGB, LGB   | SNB                         | 3.75                 | Twin     |
|  | General        | EB              | SEB                         | 3.75                 | Twin     |
|  | General        | ED              | SE6                         | 3.75                 | Twin     |
|  | General        | CED             | SCE                         | 3.75                 | Twin     |
| 150  | VL             | DG              | SDG                         | 5.00                 | Twin     |
| 225  | General        | QJ              | SQJ                         | 5.00                 | Twin     |
| 250  | General        | QR <sup>②</sup> | SQR                         | 5.00                 | Twin     |
|  | VL             | FG              | SFG                         | 5.00                 | Twin     |
|  | Sentron        | FD              | SF6                         | 5.00                 | Twin     |
|  | Sentron        | CFD             | SCF                         | 5.00                 | Single   |
| 400  | VL             | JG              | SJG                         | 6.25                 | Single   |
|  | Sentron        | JD              | SJ1                         | 8.75                 | Single   |
|  | Sentron        | CJD             | SCJ                         | 8.75                 | Single   |
|  | Sentron        | SJD             | SSJ1                        | 8.75                 | Single   |
| 600  | Sentron        | SCJD            | SSCJ                        | 8.75                 | Single   |
|  | VL             | LG              | SLG                         | 6.25                 | Single   |
|  | Sentron        | LD              | SL6                         | 8.75                 | Single   |
|  | Sentron        | CLD             | SCL                         | 8.75                 | Single   |
| 800  | Sentron        | SLD             | SSL6                        | 8.75                 | Single   |
|  | Sentron        | SCLD            | SSCL                        | 8.75                 | Single   |
| 800  | VL             | MG              | MG1                         | 8.75                 | Single   |

### Cover Plates

| For use with Sentron Shallow Depth or Type SPP/FPP/F1/P4 power panels |                   |
|---|-------------------|
| Breaker Type  | Catalog Number    |
| QR  | SQRC <sup>⑥</sup> |

### Service Entrance Barriers

| Field installable Barriers to meet UL 67 service entrance requirements |                |
|--|----------------|
| Breaker Type   | Catalog Number |
| S)JD, (S)LD, MG  | SEBP4V1        |
| CJD, CLD   | SEBP4V2        |
| JG, LG   | SEBP4V3        |

### Blank Plates — Circuit Breaker and Vacu-Break

| For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards |                |
|--|----------------|
| Height (inches)  | Catalog Number |
| 1.25   | 6FPB01         |
| 2.5  | 6FPB02         |
| 3.75   | 6FPB03         |
| 5.0  | 6FPB05         |
| 10.0   | 6FPB10         |

### Filler Plates

| For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards |                             |
|--|-----------------------------|
| Breaker Type   | Filler Plate Catalog Number |
| BL, BLH, HBL<br>ED2, ED4, ED6<br>HED4, NGB, HGB, LGB                   | DFFP1 <sup>⑤</sup>          |
| NEB, HEB   | EBF1                        |

### Connecting Strap Kits<sup>④</sup>

| For use with Sentron Shallow Depth or Type SPP/FPP/F1/P4 power panels |                      |                |
|---|----------------------|----------------|
| Ampere Rating   | Unit Height (inches) | 10" Deep Box   |
|   |                      | Catalog Number |
| 30-30   | 2.5                  | F602           |
| 30-60   | 5, 7.5               | F657           |
| 30-60   | 5, 7.5               | F657           |
| 60-60   | 5, 7.5               | F657           |
| 60-100  | 5, 7.5               | F657           |
| 100-100   | 5, 7.5               | F657           |
| 100   | 7.5                  | F657           |
| 200   | 7.5                  | F657           |
| 200   | 10                   | F671           |
| 200-200   | 10                   | F672           |

For inches / millimeters conversion, see Application Data section.

① Includes housing frame plate without breaker handle opening. Provisions include all necessary mounting hardware less breakers.  
 ② For Class J, R or T fuse clip prices, refer to page 11-57.  
 ③ For Class J fuse clips price 600V, 7½" high units.

④ NEC fuse clips only.  
 ⑤ Normal stock item.  
 ⑥ Suitable to replace QF3 in P1 thru P5 Panelboards and Switchboards.

⑦ To replace a QJ with a QR only a new cover is needed up to 225A  
 ⑧ Although QR is rated 250A, it is limited to 225A in panelboard.