

## Pipe and Conduit Seals

Rubber-insulated end caps for commercial pipes and conduits.

### Flood-Seal® Pipe/Conduit Seals

- Flood-Seal® EPDM rubber seals out water, insects, rodents and dirt
- Durable unaffected by sun, rain or soil
- Easily removable
- Ideal for installations or cable replacements
- Tight fitting to prevent accidental removal



CAT. NO.	PIPE SIZE (IPS)	STYLE	RANGES		OUTSIDE BODY LENGTH	
			CONDUCTOR	DECIMAL		
CIC 75-3	¾	10	#14-#10	—	1½	
CIC 50-3	½	10	#14-#10	—	1⅜	
CIC 1-4	1	4	(4)#14-#4	SL-.380	2⅜ <sub>32</sub>	
CIC 150	1½	5	—	.720-1.200	1⅝	
CIC 15-320		6	(3)#2-2/0	.370-.580	1⅝	
CIC 15-420		6	(4)#2-2/0	.370-.580	1⅝	
C-5230	2	4	(2)#14-350, (1)#14-1/0	SL-.910, SL-.540	1½	
C-5035		4	(1)#14-400, (1)#14-500	SL-.980, SL-1.175	1⅝ <sub>16</sub>	
C-5231		4	(3)#14-350, (1)#14-4/0	SL-.980, SL-.690	2	
CIC 200		5	—	1.093-1.562	2	
CIC 201	5	—	.937-1.145	4		
PS 2	7	—	(3)#14-250	SL-.765	1⅝ <sub>16</sub>	
3133	2½	2	300-1500	.760-1.880	2⅝	
3133-6		2	300-1500	.760-1.880	6⅝	
CIC 25-440		4	(4)#2-4/0	.390-.690	2¼	
CAP 250		1	NA	NA	3	
PS 25	7	—	(2)#14-350, (1)#14-250	SL-.980, SL-.765	1⅝ <sub>16</sub>	
3135	3	2	350-2000	.830-2.234	2½	
CAP 300		1	NA	NA	2½	
CVC 3*		6	—	(3)1.093-1.562	2⅝ <sub>16</sub>	
CNC 3-1G		9	—	(1)1.031-1.531, (1).280-.420	2½	
PS 3	7	—	(3)#14-350, (1)#14-250	SL-.980, SL-.765	1⅝ <sub>16</sub>	
PSX 3	3½	9	(3)#14-350, (1)#14-250	SL-.980, SL-.765	2½	
PSX 35		8	(3)#14-500, (1)#14-250 & 350-500	SL-1.175 SL-.765	3⅝ <sub>16</sub>	
3138		4	#14-400	SL-.980	2	
6318	4	3	—	1.500-3.00	2⅝ <sub>16</sub>	
CAP 400		1	NA	NA	2⅝ <sub>16</sub>	
CNC 4-1G		9	—	(1)1.031-1.531, (1).280-.420	2⅝	
CVC 4*		6	—	(3)1.125-1.875	3⅝ <sub>16</sub>	
PS 4		7	—	(3)#14-500, (1)#14-350	SL-1.175, SL-.980	1¾
CIC 401		2	—	.830-2.234	3⅝	
CAP 500		1	NA	NA	2⅝ <sub>16</sub>	
CVC 5*	6	—	1.250-2.00	3⅝ <sub>16</sub>		
PS 5	7	—	(3)#2-1500, (1)#14-500	.370-1.600, SL-1.175	2⅝	
PS 6	6	7	(4)#2-1500	.370-1.600	2¾	

\* Vent cap, not watertight.

Note: For sizes not listed, please consult your Thomas & Betts representative.

