



- CUP/CUPX/PLUG 1, 2, & 3, PLUG 1, 2, & 3-SQ
 Class I Groups A,B,C,D
 Class I, Zone 1, Groups IIC, IIB, IA
 Class II Groups E,F,G
- CUP/CUPX/PLUG 1 1/4" through 4"
 Class I, Groups C,D
 Class I, Zone 1, Groups IIB, IIA
 Class II Groups E,F,G

UL Standard: 886
 CSA Standard: C22.2 No. 30

Listed File No. E 10514
 Certified File No. LR11716

FEATURES-SPECIFICATIONS

Application

- To close up a taped hole or hub

Features

- Threaded hubs (NPT)

Material/Finish

Copper-free Aluminum — 1/4" - 4"
 (less than 4/10 of 1%)

- Natural Finish

Steel — 1/2" - 1"

- Zinc Plated

Iron — 1-1/4" - 4"

- Zinc Plated

RECESSED PLUG		
CATALOG NUMBER		HUB SIZE
KILLARK ALUMINUM	STEEL/IRON	
CUP-375	PLUG375	3/8"
CUP-1	PLUG1	1/2"
CUP-2	PLUG2	3/4"
CUP-3	PLUG3	1"
CUP-4	PLUG4	1-1/4"
CUP-5	PLUG5	1-1/2"
CUP-6	PLUG6	2"
CUP-7	PLUG7	2-1/2"
CUP-8	PLUG8	3"
CUP-9	PLUG9	3-1/2"
CUP-0	PLUG10	4"

SQUARE HEAD PLUG		
CATALOG NUMBER		HUB SIZE
KILLARK ALUMINUM	STEEL/IRON	
CUPX-250	—	1/4"
CUPX-1	PLUG1-SQ	1/2"
CUPX-2	PLUG2-SQ	3/4"
CUPX-3	PLUG3-SQ	1"
CUPX-4	PLUG4-SQ	1-1/4"
CUPX-5	PLUG5-SQ	1-1/2"
CUPX-6	PLUG6-SQ	2"
CUPX-7	PLUG7-SQ	2-1/2"
CUPX-8	PLUG8-SQ	3"
CUPX-9	PLUG9-SQ	3-1/2"
CUPX-0	PLUG10-SQ	4"

Listed File No. E 311892



AN

Applications

- To connect threaded on IMC conduit to cast hubs on drilled and tapped conduit openings

Features

- Tapered threads (NPT)

Material/Finish

Copper-free Aluminum
 (less than 4/10 of 1%)

RIGID CONDUIT NIPPLES				
CLOSE	BODY LENGTH	CATALOG NUMBER		CONDUIT SIZE
		2" LONG	BODY LENGTH	
AN-1	1-1/2"	AN-1B	2"	1/2"
AN-2	1-37/64"	AN-2B	2"	3/4"
AN-3	2"	AN-3B	2"	1"
AN-4	2-1/64"	—	—	1-1/4"
AN-5	2-1/16"	—	—	1-1/2"
AN-6	2-1/8"	—	—	2"
AN-7	3-9/64"	—	—	2-1/2"
AN-8	3-17/64"	—	—	3"
AN-9	3-23/64"	—	—	3-1/2"
AN-10	3-15/32"	—	—	4"
AN-11	3-1/2"	—	—	5"
AN-12	3-1/2"	—	—	6"

