

**U5200 STANDARD MODELS**






SINGLE HEAD CATALOG #	DBL. HEAD CATALOG#	RECEPTACLES	CIRCUIT BREAKERS
◆ U5200-XL-41 U5200-XL-41GB	◆ U5220-XL-41	(1) TT30R (1) 5-20R GFI  (1) TT30R (1) 5-20R	(1) 30A, 1P, 120V (1) 20A, 1P, 120V  (1) 30A, 1P, 120V (1) 20A, 1P, 120V, GFI
◆ U5200-XL-332		(2) TT30R (1) 5-20R GFI	(2) 30A, 1P, 120V (1) 20A, 1P, 120V
◆ U5200-XL-75 U5200-XL-75GB	◆ U5220-XL-75	(1) 14-50R (1) TT30R (1) 5-20R GFI  (1) 14-50R (1) TT30R (1) 5-20R	(1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V  (1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V, GFI

**U5200 STANDARD BASE MODELS**

Order up to (3) receptacle / breaker kits. Sold separately for field installation.

CATALOG #	DESCRIPTION
◆ U5200-XL	Single head base model on direct burial post.
◆ U5210-XL	Single head base model on pad mount post. Order <b>K5410</b> pad mount base separately.
◆ U5220-XL	Double head base model on direct burial post.
◆ U5230-XL	Double head base model on pad mount post. Order <b>K5410</b> pad mount base separately.

**RECEPTACLE & CIRCUIT BREAKER KITS**

CATALOG #	RECEPTACLES	CIRCUIT BREAKERS	CONDUCTORS	CONFIGURATION
◆ K5400-520GR	5-20R Duplex GFI	20 Amp, 1 Pole	12 Awg	 GFI Rec.
◆ K5400-520GB	5-20R Duplex	20 Amp, 1 Pole GFI	12 Awg	 GFI CB
◆ K5400-TT30	TT30R	30 Amp, 1 Pole	10 Awg	
K5400-TT30GB	TT30R	30 Amp, 1 Pole GFI	10 Awg	 GFI CB
◆ K5400-1450	14-50R	50 Amp, 2 Pole	8 Awg	

◆ Stock model. Availability subject to prior sale.

Note: 20 Amp GFI required at each RV site by UL and NEC 551-71

**INTERNAL LIGHT KITS** Factory or field installed. See accessory page.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements before ordering or installing equipment in this catalog.