

Operating heads, complete or for customer assembly



Complete switch

=



Body/contact assembly

+



Head

+



Lever

Rotary or multi-directional heads

Metal head with thermoplastic roller lever

Metal head with steel roller lever

With variable length thermoplastic roller lever (4)

With Ø6 mm thermoplastic rod 200 mm (5)

With thermoplastic roller lever (5) for actuation from left AND right or left OR right

With cat's whisker

With spring rod



Catalog number ↻ ZCKD15

↻ ZCKD16

ZCKD41

ZCKD59

↻ ZCKD31

ZCKD06

ZCKD08

Plunger heads

With metal end plunger

With metal end plunger and protective boot

With steel roller plunger

With steel roller plunger and protective boot

With thermoplastic roller-lever plunger, horizontal actuation in 1 direction

With steel roller-lever plunger, horizontal actuation in 1 direction



Catalog number ↻ ZCKD10

↻ ZCKD109

↻ ZCKD02

↻ ZCKD029

↻ ZCKD21

↻ ZCKD23

Rotary heads and separate levers

Spring return, selectable, for actuation from left AND right or left OR right

Spring return, selectable, for actuation from left AND right or left OR right

Lever with thermoplastic roller (4)

Lever with steel roller (4)

Variable length lever with thermoplastic roller (4)

Variable length lever with steel roller (4)

Rod, Ø6 mm thermoplastic 200 mm (4)



Catalog number ↻ ZCKG00

↻ ZCKD05

↻ ZCKY31

↻ ZCKY33

ZCKY41

ZCKY43

ZCKY59

(4) Adjustable throughout 360° in 5° steps, or in 90° steps by reversing the notched washer.

(5) Adjustable throughout 360° in 5° steps, or in 45° steps by reversing the lever mounting.

↻ Positive opening operation.