

SUPERBAY BI SERIES

14" ALUMINUM
REFLECTOR

Cat. #		Approvals
Job	Type	



APPLICATIONS


- Narrow, medium and wide lighting distributions for applications flexibility.

SPECIFICATIONS

- Anodal® finished 14" diameter spun aluminum reflector.
- Field adjustable brackets provide narrow, medium and wide lighting distributions.
- Rugged, two-piece, die cast aluminum ballast housing with corrosion-resistant Lektrocote® white finish.
- Unit Pack available, see table below (lamp included in Unit Pack).

LISTINGS

- Up to 55°C ambient, suitable for damp location, minimum 90°C supply conductors.



	A	B	C	D	E	F
SLICK-ON®	22 ³ / ₁₆ "-24 ⁷ / ₁₆ "	14 ¹ / ₄ "	9 ¹ / ₂ "	9 ⁷ / ₁₆ "	9 ¹ / ₂ "	2"
	564-621 mm	362 mm	241 mm	240 mm	241 mm	51 mm
QUICK-ON®	21 ⁵ / ₁₆ "-23 ⁹ / ₁₆ "	14 ¹ / ₄ "	8 ⁵ / ₈ "	9 ⁷ / ₁₆ "	9 ¹ / ₂ "	1 ¹ / ₈ "
	541-598 mm	362 mm	219 mm	240 mm	241 mm	29 mm



ORDERING INFORMATION

ORDERING EXAMPLE

BL	-	400		P		8	-	BI	-	WH
Series		Wattage		Source		Voltage		Optics		Color

SERIES

BL Superbay Series

WATTAGE

150	150 watt HPS
175	175 watt MH or Pulse Start MH
200	200 watt Pulse Start MH only
250	250 watt MH, Pulse Start MH or HPS
320	320 watt Pulse Start MH only
350	350 watt Pulse Start MH or Electro-Reg®
400	400 watt MH, Pulse Start MH, HPS or Electro-Reg®
450	450 watt Pulse Start MH only

SOURCE

H	Metal Halide (export only)
S	High Pressure Sodium
P	Pulse Start Metal Halide
E	Electro-Reg® (40°C)

VOLTAGE

1	120V Electro-Reg®
2	208V Electro-Reg®
3	240V Electro-Reg®
4	277V Electro-Reg®
5	480V
6	Tri-Tap® - 120/277/347V
7	600V (isolated secondary only)
8	Quad-Tap® (multi-tap) - 120/208/240/277V
F	347V

OPTICS

BI 14" Spun Aluminum Highbay Reflector with uplight

BOTTOM ENCLOSURE

BL-LR-14 Bottom Enclosure

COLOR

WH White (standard)
GR Gray (optional)

NOTE: MV lamp will operate on MH ballast.

NOTE: Energy Saving Linear Reactor Pulse Start ballast available, consult factory (277V only).

NOTE: Bottom enclosures are required unless lamps designated as "suitable for open use" are used.

NOTE: Options must be added as suffix to Catalog Number. Accessories must be ordered separately.

BI UNIT PACKS

MATERIAL	MATERIAL DESCRIPTION	WATTAGE	VOLTAGE	LAMP BASE	LAMP INCLUDED
METAL HALIDE PULSE START					
BL320P8BCEXUPL	BL-320P8-BC-WH-EX-UPL	320	Quad-Tap	Exclusionary	Lamp Included
BL320P8BCWHUPL	BL-320P8-BC-WH-UPL	320	Quad-Tap	Mogul	Lamp Included
BL400P8BCEXUPL	BL-400P8-BC-WH-EX-UPL	400	Quad-Tap	Exclusionary	Lamp Included
BL400P8BCWHUPL	BL-400P8-BC-WH-UPL	400	Quad-Tap	Mogul	Lamp Included
HIGH PRESSURE SODIUM					
BL400S8WHBIUPL	BL-400S8-WH-BI-UPL	400	Quad-Tap	Mogul	Lamp Included