



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YTA28R2N  
 7818100139777  
 4/0 AL/CU/ACSR T SLOTTED  
 Active

**Web Use**  
 BURNDY Product Line

Bolt Size as a fraction  
 Drilling Configuration  
 Length (in)  
 Thickness (in)  
 Bolt Hole Spacing  
 E - in  
 Length (Fraction)

**Dimensional**

1/2  
 2 Hole NEMA slotted  
 7.875  
 1/2  
 1-3/4  
 1.75  
 7-7/8

**General**

AL primary T-tap connector with slotted tap pad designed for easy disconnecting of tap conductor, For use with Types YKA-R-2N and YKA-A-2N, Width:1.00 IN L

Product Description

**Conductor(s)**

ACSR Size (Range)  
 AAAC 6201 Size (Range)  
 Aluminum Size (Range)  
 Copper Stranded (Range)  
 AAAC 5005-Size (Range)

4/0 (6/1) Penquin AWG  
 246.9 (7) kcmil  
 4/0 AWG  
 4/0 AWG  
 246.9 (7) kcmil

**Physical**

Index Number

251,L

**Approvals / Certifications**

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS

N  
 N  
 Compliant  
 N  
 N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175

