

Surge Protected Duplex Outlet Kit

364569-02-V1



Duplex outlet power kits are an easy-to-use solution to providing power for system modules. Surge suppression provides protection for hot to neutral, hot to ground, and neutral to ground. The audible alarm signals when surge protection has expired. This kit includes duplex power outlet, metal "J" box, and faceplate kit. It can be used in On-Q Custom, Premium and Value-Line Enclosures.

features & benefits

- Includes electrical box, white duplex receptacle and white faceplate
- The audible alarm signals when surge protection has expired
- 120 VAC
- 15 A

specifications

General Info

Color: White

Termination:

Brass HOT
Nickel NEUTRAL
Green GROUND

Type: Surge-Suppressing Outlet

Housing Material: Metal

Input Plug Type: NEMA 5-15R Male

Number Of Poles: 2

Number Of Wires: 3

Assembly/Installation Information

Mounting Hardware Included: Screws

Listing Agencies/Third Party Information

UN SPS C: 39121610

Construction Information

Installation Location: On-Q enclosures

Dimensions

Depth Metric: 4.8 cm

Depth U S: 1.9"

Height Metric: 11.4 cm

Height U S: 4.5"

Width Metric: 7 cm

Width U S: 2.75 in

Technical Information

AC Voltage Output: 120 VAC

Amps: 15A

Connection Method: Screw terminal

Frequency: 60 Hz

Material: Thermoplastic

Max Surge Current: 9kA

Mounting: Enclosure base

Noise Reduction: 7:1

Operating Temperature Celsius: -20°C to 55°C

Operating Temperature Fahrenheit: -4°F to 131°F

Product Fits Into: Single-Gang

Storage Temperature: -40°C to 85°C

Wire Gauge: 10 - 14 AWG, copper conductor only

Receptacle Type: NEMA 5-15R Female

Number Of Receptacles: 2

Surge Suppression: UL1449 Transient Voltage Surge Suppressor