



# Bolts



## Double Arming

Double arming bolts are fully threaded and used in double crossarm construction to secure and lock in spacing between crossarms

### Features

- Fully threaded and assembled with 4 square nuts
- Ends can accept eyenuts for deadend applications
- Length dimensions do not include points

### Material

Steel hot dip galvanized

| 5/8" Diameter - Minimum Tensile Strength 13,550 lbs |                  |                   |
|---|------------------|-------------------|
| Catalog Number                                      | Bolt Length (in) | Weight /100 (lbs) |
| J8860   | 10               | 118               |
| J8862   | 12               | 136               |
| J8864   | 14               | 142               |
| J8866   | 16               | 158               |
| J8868   | 18               | 187               |
| J8870   | 20               | 192               |
| J8872   | 22               | 208               |
| J8874   | 24               | 224               |
| J8876   | 26               | 240               |
| J8877   | 28               | 256               |
| J8878   | 30               | 264               |
| J8879   | 32               | 284               |
| J8880   | 34               | 295               |
| J8881   | 36               | 332               |

| 3/4" Diameter - Minimum Tensile Strength 20,050 lbs |                  |                   |
|---|------------------|-------------------|
| Catalog Number                                      | Bolt Length (in) | Weight /100 (lbs) |
| J8883   | 10               | 163               |
| J8882   | 12               | 196               |
| J8884   | 14               | 220               |
| J8886   | 16               | 240               |
| J8888   | 18               | 260               |
| J8890   | 20               | 284               |
| J8892   | 22               | 304               |
| J8894   | 24               | 336               |
| J8896   | 26               | 345               |
| J8897   | 28               | 365               |
| J8898   | 30               | 386               |
| J8899   | 32               | 400               |
| J9003   | 34               | 420               |
| J9004   | 36               | 460               |

| 7/8" Diameter - Minimum Tensile Strength 27,700 lbs |                  |                   |
|---|------------------|-------------------|
| Catalog Number                                      | Bolt Length (in) | Weight /100 (lbs) |
| J9112   | 12               | 283               |
| J9114   | 14               | 312               |
| J9116   | 16               | 341               |
| J9118   | 18               | 370               |
| J9120   | 20               | 399               |
| J9122   | 22               | 427               |
| J9124   | 24               | 456               |
| J9126   | 26               | 485               |
| J9128   | 28               | 514               |
| J9130   | 30               | 543               |
| J9132   | 32               | 572               |
| J9134   | 34               | 601               |
| J9136   | 36               | 630               |
| J9138   | 38               | 659               |
| J9140   | 40               | 688               |
| J9142   | 42               | 717               |