

ROTARY LASERS



Self-Leveling Int/Ext Rotary Laser Package



Self Leveling Interior Rotary Laser - Combo Kit



Self Leveling Rotary Laser - Combo Kit w/ Detector (Int/Ext)



Self-Leveling Int/Ext Rotary Laser Kit

SPECIFICATIONS

	DW079KDT	DW079KI	DW079KD	DW074KDT
Power Supply	9.6V-18V DeWALT batteries	9.6V-18V DeWALT batteries	9.6V-18V DeWALT batteries	(2) D Alkaline batteries
Accuracy per 100 ft.	1/8"	1/8"	1/8"	1/4"
Rotation Speed	0, 60, 250, & 600 rpm	0, 60, 250, & 600 rpm	0, 60, 250, & 600 rpm	0, 60, & 600 rpm
Self-Leveling Range	±5°	±5°	±5°	±5°
Indoor Visibility Range	200' (dia)	200' (dia)	200' (dia)	100' (dia)
Range with Detector	2,000' (dia)	2,000' (dia)	2,000' (dia)	600' (dia)
Laser Class	Illa (<5 mW) at 635 nm	Illa (<5 mW) at 635 nm	Illa (<5 mW) at 635 nm	Illa (<5 mW) at 635 nm
Slope (Single Axis)	Manual Slope ±5°	Manual Slope ±5°	Manual Slope ±5°	-
Charger/Batteries	1-Hour Charger / (1) 18V	1-Hour Charger / (1) 18V	1-Hour Charger / (1) 18V	-
Includes	Wall mount, wireless (IR) remote control, laser target card, laser enhancement glasses, construction tripod - DW0736	Wall mount, wireless (IR) remote control, laser target card, laser enhancement glasses	Wall mount, wireless (IR) remote control, laser target card, laser enhancement glasses, digital laser detector	DW0742 Detector and clamp, Target card, DW0740 Wall mount, DW0737 tripod, DW0748 8' grade rod, (2) D Alkaline batteries, & (1) 9V battery



Self-Leveling Int/Ext Rotary Laser Kit



Self Leveling 3-Beam Line Laser



Self-Leveling Line Laser (Horizontal and Vertical)



Self Leveling 3-Beam Line Laser

SPECIFICATIONS

	DW074KD	DW089K	DW087K	DW083K
Power Supply	(2) D Alkaline batteries	(4) AA batteries	(3) AA batteries	(4) AA batteries
Accuracy per 100 ft.	1/4"	1/8" at 30'	1/8" at 30'	1/4"
Rotation Speed	0, 60, & 600 rpm	-	-	-
Self-Leveling Range	±5°	±5°	±5°	±4°
Indoor Visibility Range	100' (dia)	50' (dia)	50' (dia)	100' (dia)
Range with Detector	600' (dia)	-	-	-
Laser Class	Illa (<5 mW) at 635 nm	II	II	2 (<1.5 mW) at 635 nm
Slope (Single Axis)	-	-	-	-
Charger/Batteries	(2) D Alkaline batteries	(4) AA batteries	(3) AA batteries	(4) AA batteries
Tool Weight	4.5 lbs	1.9 lbs	1.2 lbs	1.0 lbs
Includes	DW0742 Digital laser detector, DW0740 Wall mount, Target card, (2) D Alkaline batteries	Ceiling mount, (4) AA batteries	Ceiling mount, (3) AA batteries	(4) AA batteries

OPTICAL INSTRUMENTS



PAGE 44

VACUUMS



18V XRP™ 1/2 Gallon Wet/Dry Portable Vac



18V 1/2 Gallon Wet/Dry Portable Vac (Tool Only)



18/20V MAX* Wet-Dry Vacuum



18/20V MAX* Cordless/Corded Wet-Dry Vacuum

SPECIFICATIONS

	DCS15K	DCS15B	DCV580	DCV581H
Tank Size	1/2 gallon	1/2 gallon	2 gallon	2 gallon
Hose Diameter	1-1/4"	1-1/4"	1-1/4"	1-1/4"
Hose Length	2.5'	2.5'	5.0'	5.0'
Volts / Power Source	18V	18V	18V or 20V MAX*	18V or 20V MAX* or AC/DC Power
Blower	No	No	Yes	Yes
Weight	6.0 lbs	3.6 lbs (tool only)	10 lbs	10.5 lbs
Charger/Batteries	1-Hour Charger / (1) 18V XRP™	Sold Separately	Sold Separately	Sold Separately
Filter Type	High Efficiency Gore™ HEPA	High Efficiency Gore™ HEPA	High Efficiency	HEPA Rated Filter
Includes	-	-	Crevice Tool Attachment and Wide Nozzle Tool Attachment	Crevice Tool Attachment and Wide Nozzle Tool Attachment